

PAGE START DATE: 8/20/96
PAGE START TIME: 9:28: 0
DATA FILE: 5

DELTA TIME HRS	DEPTH FEET	TEMPERATURE 'F	COMMENTS
0.000	20.00	77.00	
0.317	490.00	79.00	BREAK
0.333	531.00	83.25	
0.342	553.00	149.25	
0.350	576.00	136.00	
0.367	623.00	160.50	
0.383	672.00	91.50	
0.392	698.00	105.50	
0.400	724.00	84.00	
0.408	749.00	85.00	
0.433	830.00	81.75	
0.483	1005.00	83.50	
0.625	1521.00	81.25	
0.642	1578.00	82.50	
0.683	1725.00	79.75	
0.700	1783.00	84.00	
0.725	1873.00	83.75	
0.733	1904.00	87.50	
0.750	1965.00	86.50	
0.767	2027.00	90.25	
0.817	2221.00	88.50	
0.833	2287.00	89.50	
0.858	2389.00	88.75	
0.867	2423.00	89.75	
0.917	2633.00	89.00	
0.933	2680.00	91.00	M.D.R.

DATE AND TIME CEMENT JOB COMPLETE:

AUGUST 19, 1996 @ 4:55 PM

DATE AND TIME SURVEY MADE:

AUGUST 20, 1996 @ 9:30 AM

AMOUNT AND TYPE CEMENT USED:

520 SACKS PREMIUM PLUS HALLIBURTON
LIGHT, ¼# FLOSEAL, 5# GILSONITE;
120 SACKS PREMIUM PLUS CLASS "C",
6/10% HALAD 322, 5# SALT RUN BEHIND
2746' of 5½" CASING IN A 7-7/8"
HOLE.

DEPTH FIGURED FROM:

GROUND LEVEL