

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.

30-015-29044

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-1051-7

7. Lease Name or Unit Agreement Name

MILLMAN "11" STATE

8. Well No.

4

9. Pool name or Wildcat

MILLMAN; (QU-GB-SA), EAST

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

MARALO, INC.

3. Address of Operator

P. O. BOX 832, MIDLAND, TX 79702

4. Well Location

Unit Letter 0 : 660 Feet From The SOUTH Line and 1830 Feet From The EAST Line

Section

11

Township

19S

Range

28E

NMPM

EDDY

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3423'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08/20/96 SPUD WELL @ 6:30PM, RIG REPAIR.

08/22/96 11 HRS DRILLED SURFACE HOLE & CIRC'D HOLE CLEAN FOR 8-5/8" CSG. RUN 16 JTS 8-5/8" SURFACE CSG, SET @ 650', CEMENT 8-5/8" CSG W/450 SXS CLASS "C" PREM PLUS CEMENT + 1/4# FLOCELE + 2 1/2 CACL2. CEMENT CIRC TO SURFACE. 7 HRS WOC, WELD ON 8-5/8" BRADENHEAD, NU BOP AND TEST BOP TO 1000 PSI, OK.

08/28/96 DEPTH OUT 2700' TD. 4 HRS. CIRC HOLE AND TOH TO RUN LOGS. RAN GR/CNL/LDT/DLL/MSFL FROM TD TO CSG W/GR/CNL SURFACE. RU AND RAN 64 JTS 5-1/2" 15.50# K-55 CSG. SET @ 2700', CIRC CSG. RU HALCO & CEMENT 5-1/2" CSG W/220 SXS HALCO LIGHT CEMENT W/1/4# FLOCELE + 5# SALT + 150 SXS CL. "C" PREM PLUS CEMENT W/5# SALT + .4# HALAD 322. CIRC 8 SXS CEMENT TO SURFACE, ND BOP AND SET 5-1/2" CSG SLIP, CUT OFF 5-1/2" CSG, RIG DOWN AND RELEASE RIG.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Dorothea Logan*

TITLE

REGULATORY ANALYST

DATE SEPT. 16, 1996

TYPE OR PRINT NAME

DOROTHEA LOGAN

TELEPHONE NO. 915 684-7441

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE SEP 19 1996

CONDITIONS OF APPROVAL, IF ANY: