

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-015-29045

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
E-1051-7

7. Lease Name or Unit Agreement Name

MILLMAN "11" STATE

8. Well No.
5

9. Pool name or Wildcat
MILLMAN; (QU-GB-SA), EAST

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
MARALO, INC.

3. Address of Operator
P. O. BOX 832, MIDLAND, TX 79702

4. Well Location
Unit Letter P : 810 Feet From The SOUTH Line and 660 Feet From The EAST Line

Section 11 Township 19S Range 28E NMPM EDDY County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3410'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08/31/96 SPUD WELL @ 1:00PM.

09/01/96 RAN 16 JTS 48# H40 8-5/8" 8RD CSG, SET @ 641'. CIRC CSG, RU HALCO & CEMENT 8-5/8" CSG W/450 SXS PREM PLUS CL. "C" CEMENT W/2% CACL2. CEMENT CIRC'D TO SURFACE. NU BOP AND TEST BOP TO 1000 # PSI, OK. 8 HRS. WOC, DRLED FLOAT & 40' CEMENT.

09/06/96 DEPTH OUT 2700'. CIRC'D HOLE FOR 5-1/2" CSG, LD DP & DC. RU & RAN 63 JTS 5-1/2" 8RD CSG. SET @ 2700'. RU HOWCO AND CEMENT 5-1/2" CSG W/225 SXS HALCO LIGHT PREM PLUS CEMENT + 150 SXS CL. "C" PREM CEMENT W/1/4# FLOCELE + 5# GILSONITE + .6% HALAD 322. CIRC'D 22 SXS CEMENT TO SURF. ND BOP & SET 5-1/2" CSG SLIPS AND JET PITS. RELEASED RIG.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dorothea Logan TITLE REGULATORY ANALYST DATE SEPT. 16, 1996

TYPE OR PRINT NAME DOROTHEA LOGAN TELEPHONE NO. 915 684-7441

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE SEP 19 1996

CONDITIONS OF APPROVAL, IF ANY: