S. 1st Artesia, NM 50-5 DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT INTRIPLICATION SUNDRY NOTICES AND REPORTS ON WELLS of use this form for proposals to drill or to deepen or reentry to a different reservoir Use "APPLICATION FOR PERMIT" for such proposals Engineer Deservoir SUBMIT IN TRIPLICATE of Well Of Well Of Well Of Well Of Well Of Deer SUBMIT IN TRIPLICATE of Well Of Operator TES PETROLEUM CORPORATION (505) 74/8-147.1) South 4th St., Artesia, NM 88210 IO Field and South 4th St., Artesia, NM 88210 IO Field and South 4th St., Artesia, NM 88210 IO Field and Check APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR O TYPE OF SUBMISSION IV FIL & 990' FEL of Section 15-T19S-R25E (Unit A, NENE) CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR O TYPE OF SUBMISSION IV PE OF SUBMISSION IV PE OF ACTION Subsequent Report Final Abandonment Notice Notice final Abandonment Notice I Final Abandonment Notic	Cons. Division
99-5 UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT RECEIVED Department bureau 101 BUREAU OF LAND MANAGEMENT INTED STATES INTED STATES 101 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 101 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 101 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 102 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES 103 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES 104 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES 104 Well INTED STATES INTED STATES INTED STATES 105 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES INTED STATES 104 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 105 SOUTH 4th 5t., Artesia, NM 88210 INTER STATES INTED STATES INTED STATES 105 South 4th 5th, Artesia, NM 88210 INTER STATES INTED STATES INTED STATES	Stoel 1/
99-5 UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT RECEIVED Department bureau 101 BUREAU OF LAND MANAGEMENT INTED STATES INTED STATES 101 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 101 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 101 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 102 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES 103 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES 104 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES 104 Well INTED STATES INTED STATES INTED STATES 105 SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES INTED STATES 104 INTED STATES SUNDARY NOTICES AND REPORTS ON WELLS INTED STATES INTED STATES 105 SOUTH 4th 5t., Artesia, NM 88210 INTER STATES INTED STATES INTED STATES 105 South 4th 5th, Artesia, NM 88210 INTER STATES INTED STATES INTED STATES	1 38210-2834 07
DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT INCLCETVED Budges Image: Statestop BUREAU OF LAND MANAGEMENT Image: Statestop Image: Statestop Image: Statestop Image: Statestop of use this form for proposals to drill or to deepen or reentry to a different (reserver) Image: Statestop Image: Statestop of Well Use "APPLICATION FOR PERMIT—" for such proposals Statestop Image: Statestop Image: Statestop of Well Desc SUBMIT IN TRIPLICATE Image: Statestop Image: Statestop of Well Desc AUG 1 5 1997 Image: Statestop Image: Statestop of Well Desc AUG 1 5 1997 Image: Statestop Image: Statestop of Well Desc AUG 1 5 1997 Image: Statestop Image: Statestop of Well Desc AUG 1 5 1997 Image: Statestop Image: Statestop of Well Desc AUG 1 5 1997 Image: Statestop Image: Statestop of Well Desc AUG 1 5 1997 Image: Statestop Image: Statestop of Well Desc AUG 1 5 1997 Image: Statestop Image: Statestop Image: Statestop t	ORM APPROVED
IPIT AUG - 8 A UP UP SUNDRY NOTICES AND REPORTS ON WELLS of use in for proposals to drill or to deepen or reentry to a different deservet. GMT. Use "APPLICATION FOR PERMIT" for such proposals CAU Well OF (CAU Well) SUBMIT IN TRIPLICATE Of Well OF Method Sign	a Bureau No. 1004–0135 pires: March 31, 1993 signation and Serial No.
ol use this form for proposals to drill or to deepen or reentry to a different description of the served of the se	1–023855–B
Use "APPLICATION FOR PERMIT—" for such proposition of the proposition	Allottee or Tribe Name
SUBMIT IN TRIPLICATE of Well AUG 1 5 1997 Aug 10 Operator TES PETROLEUM CORPORATION (505) 748-1471) aud Telephone No In Field and Telephone No South 4 th St., Artesia, NM 88210 Dist 2 In Field and Telephone No South 4 th St., Artesia, NM 88210 Dist 2 In Field and Telephone No CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR O TYPE OF SUBMISSION TYPE OF ACTION Abandonment Abandonment Casing & cement Operations (Clearly state all pertinent details, and give periment date, including estimated date of stating any proposed Casing & cement Checompleted Operations (Clearly state all pertinent details, and give periment	
of Well Other AUG 1 5 1997 8. Well Name of Operator (505) 74B-1471) 9. API Well TES PETROLEUM CORPORATION (505) 74B-1471) 9. API Well is of Operator (505) 74B-1471) 9. API Well is of Operator (505) 74B-1471) 9. API Well is of Operator (505) 74B-1471) 9. API Well is of Well (Postage, Sec. T. R., M. or Survey Description) 10. Field and 'S South 4th St., Artesia, NM 88210 District 2 is of Well (Postage, Sec. T. R., M. or Survey Description) 10. Field and '' FNL & 990' FEL of Section 15-T19S-R25E (Unit A, NENE) Dagger TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Other Water Abandonment Other Subsequent Report Casing Repair Other Final Abandonment Notice Casing & cement (More Report) ''' Summed drilling a 14-3/4'' hole with rotary tools at 9:15 PM 7-27-97. 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8'' 36# J 107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe se cas at set at 1060'. Cemented with 200 sacks '''', 103'' A-10B, 1/2#/sack ce cas cas gilsonite (yield 1.52, weight 14.5). and 800 sacks ''', 5#/s	r CA, Agreement Designation
Odd of Casing of Operator AUG 1 5 1997 6. Well Name Applic TES PETROLEUM CORPORATION (505) 746-1471) Applic TES petrol (505) 746-1471) 9. API Well ion of Well (Footage, Sec. T. R. M. or Survey Description) Disgr. 2 0. Field and Dagger '' FNL & 990' FEL of Section 15-T19S-R25E (Unit A, NENE) Dagger '' FNL & 990' FEL of Section 15-T19S-R25E (Unit A, NENE) Dagger '' CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR O Dagger TYPE OF SUBMISSION TYPE OF ACTION Wall Recompletion Non-F Notice of Intent Recompletion Non-F Subsequent Report Plugging Back Non-F '' Final Abandonment Notice Casing & cement Completed '' Free resumed drilling a 14-3/4'' hole with rotary tools at 9:15 PM 7-27-97. Non-F '' Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8'' 36# J 107 /2#/sack ce Loat set at 1060'. Cemented with 200 sacks ''H'', 10% A-108, 1/2#/sack ce 20 ion f Liof ake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sack ''C'', 5#/sack gilso 20 ion f 1126'. Reached TD at 12:15 AM 7-30-97. Did not bump plug. Cemetoa ion for this 106''. 1-Texas Pattern notched guide shoe se	
af Operator (505) 748-1471) Apollo TES PETROLEUM CORPORATION (505) 748-1471) 9010 ass and Telephone No. DIST.2 9010 5 South 4th St., Artesia, NM 88210 DIST.2 9010 ion of Well (Foorage, Sec. T. R. M. or Survey Description) Ion Field and Dagger 90110 '' FNL & 990' FEL of Section 15-T19S-R25E (Unit A, NENE) Dagger II. County G CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR O Inc. County G Inc. County G TYPE OF SUBMISSION TYPE OF ACTION Inc. County G Inc. County G IN Notice of Intent Abandonment Inc. County G Inc. County G IS subsequent Report Casing Repair Inc. County G Inc. County G Ithe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent of the work of the set of th	e and No.
East and Telephone No. 10. Field and 15. South 4th St., Artesia, NM 88210 DiST. 2 10. Field and Dagger 11. County G Dist. 2 11. Subsequent Report Dist. 2 11. Final Abandonment Notice	APU Fed Com #2
10. Field and Discrete Sector 1. R. M. or Survey Description) 10. Field and Dagger 1. County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of County of County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of County of Sector 15-T19S-R25E (Unit A, NENE) 11. County of County	№.)-015-29048
Y FNL & 990' FEL of Section 15-T19S-R25E (Unit A, NENE) II. County of Recompleted Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed result of casing set at 1106'. IVE as a start of the start of	Pool, or Exploratory Area
Finit & 950 Finit of Section 15-1155-R252 (onite A, MAR2) CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR O TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Subsequent Report Abandonment Final Abandonment Notice Other Resume drilling, surface Disponent Completed Operations (Clearly state all pertinent details, and give pertinent details and give pertinent details and resurrent details and resurrent details and sores pertinent to this work.)* esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. 0 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 0 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 0 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 0 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 0 1126'. Reached TD at 12:15 AM 7-30-97. Bian 25 joints of 9-5/8" 36# J 0 1126'. Reached TD at 12:15 AM 7-30-97. Did not bump 1/2#/sack ce 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe see 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe see 1107.94 * dia dia 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sack 1101 ake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sack 1101 ake and 2% CaCl2 (yield 1.90, Weight 12.6). Tailed in with 200 sack <tr< td=""><td>Draw Upper Penn, No.</td></tr<>	Draw Upper Penn, No.
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR O TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Chang Notice of Intent Recompletion New G Subsequent Report Plugging Back Non-F Final Abandonment Notice Altering Casing Convert Water Altering Casing Convert Water Casing & cement (Non-F Casing & cement Convert Convert Water Altering Casing Convert Subsequent Report Casing & cement Convert Water Altering Casing Convert Water Casing & cement Convert Water Casing & cement (Non-F Bitto Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and zones pertinent to this work.)* esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. D 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J Lito7.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set	s a ariali, Ginte
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Chang Notice of Intent Abandonment Note X Subsequent Report Plugging Back Note Final Abandonment Notice Casing Repair Water Resume drilling, surface Disp Casing & cement Convert give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Casing set at 1106'. 1-Texas Pattern notched guide shoe set 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set Solat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack cet 126'. Reached TD at 12:15 AM 7-30-97. Ban 25 joints of 9-5/8" 36# J 36# J 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set Solat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack cet 126's Reached TD at 12:15 AM 7-30-97. Ban 25 joints of 9-5/8" 36# J 36# J 12126'. Reached TD at 12:15 AM 7-30-97. Ban 25 joints of 9-5/8" 36# J 12107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set 1214 sack cet Cacl12 (yield 1.90, weight 12.6). Tailed in with 200 sacks "C", 5#/sack gilso 1216 sack and 2% Cacl12 (yield 1.90, weight 12.6). Tailed in with 200 sack Spotted 300 sacks "C" and 126 sacks	ldy Co., NM
Notice of Intent □ Notice of Intent □ Abandonment □ Chang □ Subsequent Report □ Plugging Back □ Notice □ Final Abandonment Notice □ Plugging Back □ Notice Casing & □ Convert □ Final Abandonment Notice □ Altering Casing □ Convert □ tibe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or completion duration and measured and true vertical depths for all markers and zones pertinent to this work.)* □ sumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J □ 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8	THER DATA
Image: Subsequent Report Image: Recompletion Image: Non-Final Abandonment Notice Image: Plugging Back Image: Non-Final Abandonment Notice Image: Final Abandonment Notice Image: Plugging Back Image: Non-Final Abandonment Notice Image: Plugging Back Image: Non-Final Abandonment Notice Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plugging Back Image: Plu	,
X Subsequent Report Plugging Back Non-F Gring Final Abandonment Notice Casing Repair Water Altering Casing Converting Casing & cement Converting Casing & cement Non-F ribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations and measured and true vertical depths for all markers and zones periment to this work.)* Plugging Back Non-F esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. PM 7-27-97. PM 7-27-97. D 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J J107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack cee ack gilsonite (yield 1.52, weight 14.5). and 800 sacks "C", 5#/sack gilson elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sack is "I" and the set of source and the set of th	e of Plans
□ Final Abandomment Notice □ Casing Repair □ Vater □ Final Abandomment Notice □ Altering Casing □ Convert Tribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set Loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack cet ack gilsonite (yield 1.52, weight 14.5). and 800 sacks "C", 5#/sack gilson 2106 Abandom 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sack 2107.97. Did not bump plug. Cemented 2006 Abours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 2107-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps 2. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce 2016 Action 2016 Action 201	Construction
Final Abandonment Notice Final Abandonment Notice Altering Casing Other Resume drilling, surface Disp Casing & cement (Note: Rep Completion ribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack ce ack gilsonite (yield 1.52, weight 14.5). and 800 sacks "C", 5#/sack gilso elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sa yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme CC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps (C. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	toutine Fracturing Shut-Off
ribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. () 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack ce ack gilsonite (yield 1.52, weight 14.5) and 800 sacks "C", 5#/sack gilson elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sa yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme OC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps () Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	rsion to Injection
Tribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. D 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack ce ack gilsonite (yield 1.52, weight 14.5) and 800 sacks "C", 5#/sack gilson elloflake and 2% CaC12 (yield 1.90, weight 12.6). Tailed in with 200 sack yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme DC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps (. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	ose Water ri results of multiple completion on Well
give subsurface locations and measured and true vertical depths for all markers and zones periment to this work.)* esumed drilling a 14-3/4" hole with rotary tools at 9:15 PM 7-27-97. (a) 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe se loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack ce ack gilsonite (yield 1.52, weight 14.5) and 800 sacks "C", 5#/sack gilso elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sa yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme CC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps C. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	or Recompletion Report and Log form.) work. If well is directionally drilled,
0 1126'. Reached TD at 12:15 AM 7-30-97. Ran 25 joints of 9-5/8" 36# J 107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe set loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack ce ack gilsonite (yield 1.52, weight 14.5) and 800 sacks "C", 5#/sack gilso ellof1ake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sa yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme DC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps C. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	·
1107.94') of casing set at 1106'. 1-Texas Pattern notched guide shoe se Loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack ce ack gilsonite (yield 1.52, weight 14.5) and 800 sacks "C", 5#/sack gilso elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sa yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme OC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps (. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	-
Loat set at 1060'. Cemented with 200 sacks "H", 10% A-10B, 1/2#/sack ce ack gilsonite (yield 1.52, weight 14.5) and 800 sacks "C", 5#/sack gilso elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sa yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme OC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and A 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps K. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduc	-55 8rd ST&C
ack gilsonite (yield 1.52, weight 14.5) and 800 sacks "C", 5#/sack gilso elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sa yield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme DC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps C. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduc esumed drilling.	11oflake and 10#/
elloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 savield 1.34, weight 14.8). PD 1:30 PM 7-30-97. Did not bump plug. Ceme OC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps C. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	nite, 1/4#/sack
DC 6 hours. Ran 1". Tagged cement at 163'. Spotted 300 sacks "C" and 4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps K. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduc esumed drilling.	cks "C" and 2% Caciz
4 7-30-97. Circulated 20 sacks. WOC. Nippled up and tested to 3000 ps (. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduce esumed drilling.	AT did not circulate
C. Drilled out at 1:00 PM 7-31-97. WOC 23 hours and 30 minutes. Reduces and 30 minutes. Reduce ACCEPTER	1 for 30 minutes,
The second se	ed hole to $8-3/4"$.
OTE: Cement job witnessed by Gene Hunt w/BLM-Carlsbad	FOR RECORD
	. 3 1997
	0 AA
reby certify that the foregoing is true and correct	
	Aug. 7, 1997
is space for Foleral or State office use)	
Date Date	
nditions of approval, if any:	
3 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any fals	- Golitions of front-last