			1 %.∴s	ons visio	-158		
Form 3160-5 June 1990)	DEPARTMENT BUREAU OF LA	D STATES OF THE INTERIOR ND MANAGEMENT	rtesia, N ⊼≘CEIVE	Budget Bureau No. 1 Expires: March 3 Lease Designation and S	1, 1993 Internal No.		
Do not use this for	n for proposals to drill	ND REPORTS ON WELL or to deepen or reentry to PERMIT—" for such propo	s' 1997 AUG 25 D a different reservoir. Bals EAU OF LIND	NM-023855	-B ibe Name		
I. Type of Well	SUBMIT II	N TRIPLICATE		1: If Unit or CA, Agreeme	ent Designation		
X Oil Gas Well Well	Other			8. Well Name and No.			
	YATES PETROLEUM CORPORATION (505) 748-1471)				Apollo APU Fed Com #2 9. API Well No.		
	St., Artesia, NM			30-015-29 10. Field and Pool, or Expl			
-	Sec. T. R. M. or Survey Desc ' FEL of Section	ripion) 15-T19S-R25E (Unit A		Dagger Draw Up 11. County or Parish, State			
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO							
TYPE OF S	TYPE OF SUBMISSION TYPE OF ACTION			l			
Notice of	Intent	Abandonment					
X Subsequen	t Report	Plugging Back		New Construction	ing		
Final Abar	adonment Notice	Casing Repair Altering Casing Other Produ	ction casing & cmt	Water Shut-Off Conversion to Injecti Dispose Water (Note: Report results of multip Completions of Recompletions	e completion on Well		
give subsurface location TD 8140'. Real 14 joints of 49 joints of and 10 joints Float shoe set Top marker set sack celloflah .35#/sack FL53 Bumped plug to 6:00 AM 8-20-9 Waiting on con	nns and measured and true vertical ached TD at 1:15 H 7" 26# N-80 sandb 7" 26# J-55 varnis of 7" 26# J-55 va t at 8140'. Float t at 7474'. Cemen ke (yield 2.07, we 2, 2% salt and 5# o 2700 psi for 5 m 97.	ertinent details, and give pertinent dates, depths for all markers and zones pertin 2M 8-18-97. Ran 200 Lasted (565.45'); 3 Shed (1990.25'); 124 Arnished (406.41') (c collar set at 8096 hted with 750 sacks eight 12.48). Taile 'sack gilsonite (yie hinutes, OK. Circul	in to this work.) joints of 7" 26# J joints of 7" 26# J Total 8150.41') of '. Bottom marker "H", 5#/sack gilso d in with 300 sack ld 1.66, weight 13	& 23# casing J-55 sandblast J-55 varnished f casing set a joint set at onite, .3% FL5 ks "C", .35#/s 3.0). PD 2:30	as follows: ed (100.30'); d (5088') t 8140'. 7575'. 2 and 1/4#/ ack FL25, AM 8-20-97.		
14. I hereby certify that the find signed	regaing is part and correct	<u>TileOperations</u>	a Technician	Date Aug. 2	1, 1997		
(This space for Federal or Approved by Conditions of approval, if		Tiule		Date			