

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1003-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
YATES PETROLEUM CORPORATION

(505) 748-1444

3. Address and Telephone No.  
105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
1980' FSL & 660' FEL of Section 35-T20S-R24E (Unit 1, NESE)

5. Lease Designation and Serial No.

NM-045276

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Preston Federal #13

9. API Well No.

30-015-29061

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn.

11. County or Parish, State

Eddy Co., NM

**12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

**TYPE OF SUBMISSION**

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

**TYPE OF ACTION**

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud, conductor, surface casing & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 26" hole with rat hole machine at 2:00 PM 11-15-97. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified BLM answering machine at 4:30 PM 11-15-97 of spud. Resumed drilling with rotary tools (14-3/4" hole) 11:30 PM 11-18-97.

TD 1100'. Reached TD at 12:15 AM 11-21-97. Ran 25 joints of 9-5/8" 36# J-55 8rd ST&C (1103.46') of casing set at 1100'. 1-Texas Pattern notched guide shoe set at 1100'. Insert float set at 1055'. Cemented with 200 sacks "H", 10% A-10B, 1/4#/sack celloflake, 10#/sack gilsonite and 1/2% CaCl<sub>2</sub> (yield 1.52, weight 14.6) and 900 sacks 65-35-6, 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl<sub>2</sub> (yield 1.90, weight 12.7). Tailed in with 200 sacks "C" with 2% CaCl<sub>2</sub> (yield 1.34, weight 14.8). PD 12:45 PM 11-21-97. Bumped plug to 500 psi, OK. Cement did not circulate. WOC 4-1/2 hours. Ran 1" and tagged cement at 105'. Spotted 150 sacks "C" with 4% CaCl<sub>2</sub>. PD 6:00 PM 11-21-97. WOC 2 hours. Ran 1". Tagged cement at 90'. Spotted 100 sacks "C" with 6% CaCl<sub>2</sub>. PD 8:30 PM 11-21-97. Circulated cement to surface. WOC. Nipped up and tested to 3000 psi for 30 minutes, OK. Drilled out at 3:30 PM 11-22-97. WOC 26 hours and 45 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: BLM notified for surface job, but did not witness. Jim Amos w/BLM-Carlsbad witnessed one-inching.

14. I hereby certify that the foregoing is true and correct

Signed

*Rusty Glen*

Title

Operations Technician

Date Nov. 25, 1997

(This space for Federal or State office use)

(CRIG. SGD.) GARY GOURLEY

Approved by

Conditions of approval, if any:

Title

Date