

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-29116
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Boyd BN
8. Well No.	5
9. Pool name or Wildcat	Dagger Draw Upper Penn, North

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line Section 14 Township 19S Range 25E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3440' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: Spud, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole at 12:00 noon 10-5-96 with rat hole machine. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia Answering Service of spud. Resumed drilling a 14-3/4" hole with rotary tools at 6:30 PM 10-10-96.

TD 1205'. Reached TD at 1:00 PM 10-12-96. Ran 27 joints of 9-5/8" 36# J-55 8rd ST&C (1209.90') of casing set at 1205'. 1-Texas Pattern notched guide shoe set at 1205'. Insert float set at 1165'. Cemented with 200 sacks "H", 10% gypsum, 1% CaCl<sub>2</sub>, 1/2#/sack celloflake and 10#/sack gilsonite (yield 1.51, weight 14.6) and 800 sacks "C", 6% gel, 10#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl<sub>2</sub> (yield 1.98, weight 12.5). Tailed in with 200 sacks "C" with 2% CaCl<sub>2</sub> (yield 1.34, weight 14.8). PD 8:30 PM 10-12-96. Bumped plug to 1000 psi, OK. Circulated 200 sacks. WOC. Nippled up and tested to 3000# for 30 minutes, OK. Drilled out at 3:30 PM 10-13-96. WOC 19 hours. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Oct. 18, 1996  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY TIM W. CUMMIS  
DISTRICT II SUPERVISOR

OCT 25 1996

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: