

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

811 S. 1st Street  
Artesia, NM 88210-2834

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-39635

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Mimosa AHS Federal #3-Y

9. API Well No.

10. Field and Pool, or Exploratory Area

~~Cemetery~~  
Undesignated Morrow

11. County or Parish, State

Eddy Co., NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

635' FSL & 330' FEL of Section 4-T20S-R24E (Unit P, SESE)

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud, conductor  
resume drilling, lost circ  
plugs

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 26" hole with rat hole machine at 1:00 PM 8-3-96. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified BLM-Carlsbad of spud. Resumed drilling a 17-1/2" hole with rotary tools at 5:45 PM 8-6-96.

Set lost circulation plugs as follows:

Plug #1: Pumped 100 sacks Class "H", 10% A-11, 1% CaCl<sub>2</sub>, 10#/sack gilsonite and 1/4#/sack celloflake. Plug set at 156'. WOC. TIH and tagged cement at 145'.

Plug #2: Pumped 100 sacks Class "H", 10% A-11, 1% CaCl<sub>2</sub>, 10#/sack gilsonite and 1/4#/sack celloflake. Plug set at 125'. WOC. TIH and tagged cement at 128'.

Plug #3: Pumped 100 sacks Class C Neat and 4% CaCl<sub>2</sub>. Plug set at 124'. WOC. TIH and tagged cement at 74'. Laid down 5 joints of drill pipe. WOC. Drilled cement from 72-184'.

AUG 21 1996

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date Aug. 13, 1996

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side