

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

U.M. Oil Cons. Div.  
211 S. 1st

FORM APPROVED  
Budget Bureau No. 1004 0135  
March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1400 ARTESIA

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FWL of Section 11-T19S-R25E (Unit E, SWNW)

5. Lease Designation and Serial No.

NM-12833

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Rio Penasco MF Fed Com #2

9. API Well No.

30-015-29255

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn. No.

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☒ Altering Casing  
☒ Other Spud, conductor,  
surface casing & cement

- ☐ Change of Plans  
☐ New Construction  
☐ Non Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 26" hole with rat hole machine at 5:00 PM 1-1-98. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified Jim Amos w/BLM-Carlsbad of spud. Resumed drilling a 14-3/4" hole with rotary tools at 6:30 PM 1-4-98.

TD 1165'. Reached TD at 4:30 PM 1-6-98. Ran 26 joints of 9-5/8" 36# J-55 8rd ST&C (1171.47') of casing set at 1165'. 1-Texas Pattern notched guide shoe set at 1165'. Insert float set at 1074'. Cemented with 200 sacks "H", 10% A-10B, 1/4#/sack celloflake and 5#/sack gilsonite (yield 1.52, weight 14.56) and 800 sacks 65-35-6, 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.66). Tailed in with 200 sacks Class "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 11:15 PM 1-6-98. Bumped plug to 750 psi, OK. Circulated 176 sacks. WOC. Nipped up and tested to 3000 psi for 30 minutes, OK. Drilled out at 11:00 PM 1-7-98. WOC 23 hours and 45 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Notified Gene Hunt w/BLM-Carlsbad of cementing - no witness.

14. I hereby certify that the foregoing is true and correct

Signed Rusty Klein  
(This space for Federal or State office use)

Title Operations Technician

Date Jan. 9, 1998

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_