## **INSTRUCTIONS**

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE Southeastern New Mexico Northeastern New Mexico

T. Salt			T. Atoka T. Miss T. Devonian T. Silurian T. Montoya T. Simpson T. McKee T. Ellenburger		T. Kirtland-Fruitland T. Pictured Cliffs T. Cliff House T. Menefee T. Point Lookout T. Mancos T. Gallup Base Greenhorn T. Dakota			T. Penn. "B" T. Penn. "C" T. Penn. "D" T. Leadville T. Madison T. Elbert T. McCracken T. Ignacio Otzte T. Granite T.
I. Iudo			1. Delaware Sand		T. Todilto			T
T. Drink	ard		T. Bone Springs	T. Bone Springs 3596'				<sup>1</sup>
T. Wolfe	amp	8672	T.1st BSGL Sand T.2nd BSGL Sand	T.1st BSGL Sand 5294" T.2nd BSGL Sand 6900"			· · · · · · · · · · · · · · · · · · ·	T. T. T.
T. Penn			T.3rd BSGL Sand	T. 3rd BSGL Sand 8115' T. Permain			T	
T. Cisco	(Bough C	9267		0.				T
No 1 fe				GAS SAN				
No 2 from			to	toto				to
No. 1, fr No. 2, fr	rom		nflow and elevation to which to the state of		se in hole.		feetfeet	ecessary)
From	То	Thickness in Feet	Lithology		From	То	Thickness in Feet	Lithology