MERIDIAN OIL KLM 5/10/90 STATE 19 COM. NO. 2 MILLMAN SOUTH, MORROW EDDY COUNTY, NEW MEXICO KB = 3508'GL = 3493'CONDITION AFTER WORKOVER 447' SURFACE CASING 13 3/8" 48# H-40 @ 447'. TOC=SURF INTERMEDIATE CASING 8 5/8" 24# K-55 2448' @ 2448', TOC=SURF 2 3/8" 4.7# N-80 LOST CIRCULATION @ 8926' HYDRIL 563 TUBING BLACK SULFUR WATER FLOW - TOC @ 8990' (TEMP) ■ GUIB. UNI-VI PKR (10K PSI) 1.781" ID SN-AT 10540' PERFORATING GUNS -PROPOSED MORROW PERFS 10585'-10597' (4 JSPF) CIBP @ 10720' W/ 35' CMT TOP MORROW PERFORATIONS 0 10748'-50' 10836'-47' 0 10769'-74' 10902'-20' 0 10789'-91' 10948'-52' 0 10798'-808' 11014'-18' 10814'-23' 11058'-62' PBTD=11110' 5 1/2" 17#&20# N80 & K55 TD = 11325'@ 11150', TOC=8990' (TEMP)