

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BLM OIL & GAS DISTRICT  
211-1st  
210-2834

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FWL of Section 11-T19S-R25E (Unit L, NWSW)

5. Lease Designation and Serial No.

NM-92748

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Serrano Federal #2

9. API Well No.

30-015-29401

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn, No.

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Production casing & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 8120'. Reached TD at 7:15 AM 7-13-97. Ran 199 joints of 7" 26# & 23# casing as follows: 15 joints of 7" 26# N-80 sandblasted (597.13'); 11 joints of 7" 26# J-55 sandblasted (431.97'); 41 joints of 7" 26# J-55 varnished (1684.41'); 114 joints of 7" 23# J-55 varnished (4682.53') and 18 joints of 7" 26# J-55 varnished (733.31') (Total 8129.35') of casing set at 8120'. Float shoe set at 8120'. Float collar set at 8077'. Bottom marker joint set at 7523'. Top marker joint set at 7091'. Pumped 150 bbls nitrified mud ahead of 700 sacks "C" (65-35-6), 5#/sack salt, 3% FL52, 1/4#/sack celloflake and 5#/sack gilsonite (yield 2.08, weight 12.5). Tailed in with 325 sacks "C" (61-15-11), 0.44% FL52, 3#/sack salt and 8#/sack gilsonite (yield 1.67, weight 13.0). PD 10:30 PM 11-14-97. Bumped plug to 2600 psi for 5 minutes, OK. Circulated 54 sacks. WOC. Released rig at 2:30 AM 11-15-97. NOTE: Displaced with 2% KCL.

Waiting on completion unit.

(ORIG. SGD.) GARY GOURLEY

ACCEPTED FOR RECORD

NOV 19 1997

BLM

RECEIVED

NOV 18 97

BLM  
ROSWELL, NM

14. I hereby certify that the foregoing is true and correct

Signed

*Gustafson*

Title Operations Technician

Date Nov. 17, 1997

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date