

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY 21 97

SUM
ROSWELL, NM

N.M. Oil Cons. Div.
811 S. 1st Street
Artesia, NM 87003

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1730' FEL of Section 10-T19S-R25E (Unit G, SWNE)

5. Lease Designation and Serial No.

LC-064488-E

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ottawa AOW Federal #6

9. API Well No.

30-015-29453

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn. No.

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drilling, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 14-3/4" hole with rotary tools at 3:30 PM 5-9-97.

TD 1220'. Reached TD at 9:00 PM 5-10-97. Ran 29 joints of 9-5/8" 36# J-55 (1224.58') of casing set at 1220'. 1-Texas Pattern notched guide shoe set at 1220'. Insert float set at 1177'. Cemented with 200 sacks "H", 10% A-10-B, 10#/sack gilsonite and 1/2#/sack celloflake (yield 1.52, weight 14.6) and 900 sacks Class C (65-35-6), 5#/sack gilsonite and 1/4#/sack celloflake (yield 1.90, weight 12.7). Tailed in with 200 sacks Class C and 2% CaCl2 (yield 1.34, weight 14.8). PD 3:15 AM 5-11-97. Bumped plug to 350 psi, OK. Cement did not circulate. WOC 4 hours. Ran 1". Tagged cement at 195'. Spotted 50 sacks Class C 4% CaCl2. PD 9:23 AM 5-11-97. WOC 1 hour. Ran 1". Tagged cement at 185'. Spotted 50 sacks Class C 4% CaCl2. PD 10:42 AM 5-11-97. WOC 1 hour. Ran 1". Tagged cement at 105'. Spotted 50 sacks Class C 4% CaCl2. PD 11:56 AM 5-11-97. WOC 1 hour. Ran 1". Tagged cement at 90'. Spotted 170 sacks Class C 2% CaCl2. PD 1:13 PM 5-11-97. Circulated 10 sacks to pit. WOC. Nippled up and tested to 500# for 15 minutes, OK. Drilled out at 3:30 AM 5-12-97. WOC 24 hours and 15 minutes. Reduced hole to 8-3/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date May 19, 1997

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: