

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-29501
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Boyd BN
8. Well No. 6
9. Pool name or Wildcat Dagger Draw Upper Penn, North

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter 0 : 660 Feet From The South Line and 1780 Feet From The East Line Section 15 Township 19S Range 25E NMPM Eddy County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3469' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 1:30 PM 12-18-97. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified Mae Morgan w/OCD-Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 3:00 AM 12-29-97.

TD 1165'. Reached TD at 11:15 PM 12-30-97. Ran 26 joints of 9-5/8" 36# J-55 8rd ST&C (1170.81') of casing set at 1165'. 1-Texas Pattern notched guide shoe set at 1165'. Insert float set at 1074'. Cemented with 100 sacks "H", 10% A-10B, 1/4#/sack celloflake, 10#/sack gilsonite and 1/2% CaCl2 (yield 1.52, weight 14.56) and 900 sacks 65-35-6, 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.66). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 8:45 AM 12-31-97. Bumped plug to 850 psi, OK. Nippled up and tested to 3000 psi for 30 minutes, OK. Drilled out at 3:15 AM 1-1-98. WOC 18 hours and 30 minutes. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Jan. 7, 1998
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JAN 15 1998

CONDITIONS OF APPROVAL, IF ANY: