

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-29710
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Patrick API
8. Well No.	6
9. Pool name or Wildcat	Dagger Draw Upper Penn, North
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3486' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line Section 10 Township 19S Range 25E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3486' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Resume drilling, surface casing & cmt <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole with rotary tools at 6:00 PM 2-15-98.

TD 1184'. Reached TD at 2:00 AM 2-17-98. Ran 27 joints of 9-5/8" 36# J-55 8rd ST&C (1186.93') of casing set at 1184'. 1-Texas Pattern notched guide shoe set at 1184'. Insert float set at 1095'. Cemented with 200 sacks "H", 10% A-10B, 1/4#/sack celloflake, 10#/sack gilsonite and 1/2% CaCl2 (yield 1.52, weight 14.5) and 900 sacks (65-35-6), 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.34, weight 14.8). PD 11:45 AM 2-17-98. Bumped plug to 980 psi, OK. Cement did not circulate. WOC 5-1/4 hours. Ran Temperature Survey and found top of cement at 380'. Ran 1". Tagged cement at 257'. Spotted 100 sacks "C" with 4% CaCl2. PD 7:20 PM 2-17-98. WOC 1 hour. Ran 1". Tagged cement at 126'. Spotted 100 sacks "C" with 4% CaCl2. Stopped pumping at 9:15 PM 2-17-98. WOC 2 hours. Ran 1". Tagged cement at 98'. Spotted 100 sacks "C" with 4% CaCl2. PD 12:00 AM 2-18-98. Circulated 8 sacks cement to reserve pit. WOC. Nipped up and tested to 3000 psi for

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE Feb. 26, 1998  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR


APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 3-12-98

CONDITIONS OF APPROVAL, IF ANY:

YATES PETROLEUM CORPORATION  
Patrick API #6  
Section 10-T19S-R25E  
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

30 minutes, OK. Drilled out at 5:30 PM 2-18-98. WOC 17 hours and 45 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: First cement job witnessed by Mike Stubblefield w/OCD-Artesia. One-inch cement not witnessed.



---

Rusty Klein  
Operations Technician  
February 26, 1998