

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-29713
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Marshall API
8. Well No.	4
9. Pool name or Wildcat	Shagger Draw Upper Penn, North
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3541' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter D : 710 Feet From The North Line and 660 Feet From The West Line
Section 9 Township 19S Range	NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Resume drilling, surface casing & cmt <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole with rotary tools at 7:00 PM 11-29-97.

TD 1142'. Reached TD at 12:30 AM 12-1-97. Ran 26 joints of 9-5/8" 36# J-55 8rd ST&C (1146.24') of casing set at 1142'. 1-Texas Pattern notched guide shoe set at 1142'. Insert float set at 1097'. Cemented with 200 sacks "H", 10% A-10B, 1/4#/sack celloflake, 10#/sack gilsonite and 1/2% CaCl2 (yield 1.52, weight 14.5) and 900 sacks 65-35-6, 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 AM 12-1-97. Bumped plug to 1200 psi, OK. Cement did not circulate. WOC 4 hours. Ran 1". Tagged cement at 195'. Spotted 300 sacks "C" with 4% CaCl2. PD 2:30 PM 12-1-97. WOC 2 hours. Ran 1". Tagged cement at 102'. Spotted 200 sacks "C" with 4% CaCl2. PD 5:00 PM 12-1-97. Circulated 30 sacks cement. WOC. Nippled up and tested to 3000 psi for 30 minutes, OK. Drilled out at 4:00 PM 12-2-97. WOC 29 hours and 45 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Cementing witnessed by Gary Williams W/OCD.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Dec. 3, 1997  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use) W. GUM  
DISTRICT II SUPERVISOR

JAN 8 1998

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: