

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-015-30071
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name Parkway "16" State Com.
Well No. 1
Pool name or Wildcat Trukey Track; Morrow 86480

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
Name of Operator Mewbourne Oil Company	
Address of Operator PO Box 5270, Hobbs, New Mexico 88240	
Well Location Unit Letter <u>M</u> : <u>860</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>West</u> Line <u>16</u> Section <u>19S</u> Township <u>29E</u> Range <u>NMPM</u> <u>Eddy</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3341 GR	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled a 7 7/8" hole to 11,550', then logged open hole. Logged with a Compensated Z-Densilog, Compensated Neutron Log, Gamma Ray Caliper, Dual Laterolog, Micro Laterolog, and Formation Multi-Tester Gamma Ray. Logger TD was 11,550'. Ran 287 joints of 5 1/2" 17# P110 and N80 LT&C. Set casing at 11,550'. Cemented in two stages. First stage we pumped 476 sacks of Interfill "H" Mod. with .5% Halad-344, 1% HR-7, 4% CFR-3 and 1#/sk Salt. Opened stage tool and circulated mud for 6 hours. Pumped second stage lead with 440 sacks of Interfill "H" with 1/4# per sack Flocele, tailed with 410 sacks of Super "H" Mod. with .5% Halad-344, .1% HR-7 .4% CFR-3, and 1#/sack Salt. Plug down at 3:15/am 3-21-99

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Matthews TITLE Drilling Superintendent DATE 03-24-99

TYPE OR PRINT NAME Steve Matthews

TELEPHONE NO. (505)393-5905

(This space for State Use)

**ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR**

APPROVED BY B6X TITLE DATE 4-8-99

CONDITIONS OF APPROVAL, IF ANY: