

CASING AND CEMENTING REPORT

LEASE & WELL NO. Shugart 28 Foot #1 DATE 11/16/91

EFFECTIVE	SETTING

LEASE & WELL NO.

Shugart 28 Feb 42

DATE 11/16/91

LEASE & WELL NO.		DATE		SETTING DEPTH	
Casing Run:		EFFECTIVE LENGTH		FROM TO	
Production 1 1/2				0"	
RKB TO CUTOFF POINT		17.5'			
NO. OF JTS.	SIZE	WT.	GRADE	THU	
205	4 1/2"	11.6	N-80	LTC 8rd	9042.36
	4 1/2"		Dr foul	8rd	1.98
#25	4 1/2"	11.6	N-80	LTC 8rd	1109.17
43	4 1/2"	11.6	S-95	LTC 8rd	1893.20
	4 1/2"		float collar	8rd	1.05
1	4 1/2"	11.6	S-95	LTC 8rd	44.50
	4 1/2"		float shoe	8rd	1.20
					130.00

MUD LINE HANGER @

FL. OAT COLLAR ②

D. V. TOOL ②

CSO WEIGHT ON HOOK 130,000

CSG WEIGHT ON SLIPS 115,000

NO. OF CENTRALIZERS 20

RECIPROCAL CSNB: YES NO FT

CASING DISPOSITION

RECEIVED - DATE

	JTS.	GRADE	WT.	LENGTH
44	S-95	11.6	1937.12	
231	A-80	11.6	10195.63	
	JTS.	GRADE	WT.	LENGTH
			12133.33	TOTAL

SENT IN - DATE

1	JTS.	N 90	GRADE 11.6	WT. 44.10	LENGTH
	JTS.		GRADE	WT. 40.5	LENGTH
	JTS.		GRADE	WT.	LENGTH
CUT OFF		N 80	GRADE 11.6	WT. 43.51	LENGTH
		+ 17.5 cut off		105.11	TOTAL

CEMENT REPORT

CEMENT REPORT

DEPTH OF SHOE	12050	DEPTH OF COLLAR	12003	TOP OF LINER	N/A
HUMP PLUG AT	9:35	ADJ. WITH	187	BRLS. @	1230
LEAD IN SLURRY:	250	SACKS	CLASS	H	PSI
3% Halad 322					PSI
TAIL IN SLURRY:	450	SACKS	CLASS	H	PSI
gilsonite, 1% HR-7, .5% H-304, 4% CFR-44					PSI
MUD RETURNS: YES	X	NO			

DEPTH STAGE COLLAR: 8999 BBLs. 3000 PSI CLOSURE O.K. YES
BUMP PLUG AT 16:45 AMM WITH 134 PLUS _____
LEAD IN SLURRY: 300 SACKS CLASS C PPG. YIELD 2.78 CF/SK
: interfill neat MIXED AT 11.7 PLUS 1st salt, 5⁺
TAIL IN SLURRY: 800 SACKS CLASS H PPG. YIELD 1.65 CF/SK
gilsonite, 1% HR-1, 5% H-344, 4% CFC-44 MIXED AT 13.0 CEMENT RETURNS: 66 (140)
MUD RETURNS: YES X NO _____

MUD RETURNS: YES 8 NO

WELLHEAD: MAKE Cameron TYPE: SFR. NO: 155912-0102-UK SIZE: 7 1/2 x 11" WP: 5000*

WELLHEAD: 5000* FOR 15 MIN. 4 OK?

REMARKS:

FORM NAME John M. Sherson