

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reenter a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE**1. Type of Well**Oil
WellGas
Well

Other

type other description or delete

2. Name of Operator

Ocean Energy, Inc.

3. Address and Telephone No.

410 17th St., STE 1400, Denver, CO 80202 (303) 573-4721

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)1980' FWL & 1650' FNL Section 28-T18S-R31E
C N/2 SE NW**5. Lease Designation and Serial No.**

LC-029390-A

6. If Indian, Allottee or Tribe Name**7. If Unit or CA, Agreement Designation****8. Well Name and No.**

Shugart 28 Federal #2

9. API Well No.

30-015-30363

10. Field and Pool, or Exploratory Area

Morrow

11. County or Parish, State

Eddy New Mexico

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**TYPE OF SUBMISSION**

Notice of Intent



Subsequent Report



Final Abandonment Notice

TYPE OF ACTION

Abandonment



Recompletion



Plugging Back



Casing Repair



Altering Casing



Other Casing Cement Report



Change of Plans



New Construction



Non-Routine Fracturing



Water Shut-Off



Conversion to Injection



Dispose Water

(Note: Report results of multiple completion on Well

Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed

work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Surface Casing: 9/12/98, 13-3/8", H-40 @ 624'. Cemented with 365 sx "C" Neat followed by 200 sx "C" w/2% CaCl.

Centralizers were placed 5' above shoe & on joints # 2,4,6,8,10, 13 & 16. Cement was circulated to surface.

Casing pressured up to 500 psi for 30 minutes, held OK.

Intermediate Casing: 9/21/98, 8-5/8", K-55 @ 4825'. Cemented with 1200 sx class "C". Cement circulated to surface.

Centralizers placed 5' above shoe & on joints # 2,4,6,8,10,14,16,20 & 24.

Casing pressured up to 500 psi for 30 minutes, held OK.

Production Casing: 10/16/98. 4-1/2", N-80 @ 12038'. Cemented with 1180 sx class "H". DV tool @ 8998'.

Shoe @ 12036'.

Centralizers 5' above shoe then on joints # 2,4,6,8,10,12,14 & @ DV tool.

14. I hereby certify that the foregoing is true and correct

Signed

Title Regulatory Coordinator

Date 12/29/98

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

(ORIG. SGD.) DAVID R. GLASS

FEB 18 1999

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

***See Instructions on Reverse Side**