

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED
Budget Bureau No: 1004-0135
Expires November 30, 2000

5. Lease Serial No.

NMLC029392-"b"

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.
Greenwood Federal Com.

27 #2

9. API Well No.

30-015-30680

10. Field and Pool, or Exploratory Area
Shugart Morrow
#85300

11. County or Parish, State

Eddy NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Acidize ☐ Deepen ☐ Production (Start/Resume) ☐ Water Shut-Off
☐ Alter Casing ☐ Fracture Treat ☐ Reclamation ☐ Well Integrity
☐ Casing Repair ☐ New Construction ☐ Recomplete ☐ Other
☐ Change Plans ☐ Plug and Abandon ☐ Temporarily Abandon
☐ Convert to Injection ☐ Plug Back ☐ Water Disposal

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

Drill 17 1/2" hole to 500'. Set 15 jts - 13 3/8" - 48# - H40 csg. Cmt: Lead - 170sks Class H + 3% D-79 + .25#/sk. Celloflake, St. 12.0 ppg Yld. 2.39 Tailed w/200sks Class C + 2% CaCl2, Wt/ 14.8 ppg, Yld 1.34. Good circulation during job, circulated 100sks to pit, floats held. Test csg to 1200 psi. 9/30/99

Drill 11" hole to 2800'. Set 63 jts - 8 5/8" - 32# - J55 csg. Cement w/600sks Class H + 3% D-79 + .25#/sk. Celloflake, wt 12.0 ppg, Yld. 2.39, tailed w/200sks Class C + 1% CaCl2, bumped plug w/1250 psi, circulated 23 Bbls cement to pit (55sks). Test BOP & choke manifold to 250/3000 psi, annular to 250/1500 psi, upper & lower Kelly vales to 250/3000 psi. Test 8 5/8" csg to 1500 psi. Test formation to 11.0 EMW - 400 psi. 10/04/99.

Drill 7 7/8" hole to 11,800'. Set 284 jts - 4 1/2" - N & HCN80 - 17# csg. Lead cement: 150sks 6% D20 Bentinote gel, 5% d44 salt, 2% antifoam. Tail w/365 sks 2% d20 Bentonite gel, 5% d44 salt, 2% antifoam. 2% recorder. Disp w/269 BBL bump plug 1800 psi OK. 10/28/99
Test csg to 3000 psi 11/05/99.

Started completion on 10/29/99.

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Title

C.O.O.

Date

11-10-99

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)