

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE  
N. M. Oil & Gas Division  
811 S. 15

FORM APPROVED  
OMB NO. 1004-0136  
Expires: February 28, 1995

ARTESIA, NM 88210-2834

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

TYPE OF WORK  
DRILL ☒ DEEPEN ☐

TYPE OF WELL  
OIL ☒ GAS ☐ OTHER ☐ SINGLE ZONE ☒ MULTIPLE ZONE ☐

NAME OF OPERATOR  
MONCHO RESOURCES, INC. (JIM BLOUNT) 915-683-7443

ADDRESS AND TELEPHONE NO.  
10 WEST LOUISIANA SUITE 410 MIDLAND, TEXAS 79701 915-683-7443

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)  
360' FEL & 360' FNL SEC. 30 T18S-R31E EDDY CO. NM  
Proposed prod. zone SAME

DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE\*  
Approximately 8 miles Southeast of Loco Hills New Mexico

DISTANCE FROM PROPOSED\*  
LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. 660'  
(Also to nearest drlg. unit line, if any)  
DISTANCE FROM PROPOSED LOCATION\*  
TO NEAREST WELL, DRILLING, COMPLETED, 330'  
OR APPLIED FOR, ON THIS LEASE, FT.

ELEVATIONS (Show whether DF, RT, GR, etc.)  
3637' GR.

5. LEASE DESIGNATION AND SERIAL NO.

CCNM-029387-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

24302

8. FARM OR LEASE NAME, WELL NO.

WEST SHUGART "30" FEDERAL # 3

9. API WELL NO.

30-CIS-30776

10. FIELD AND POOL, OR WILDCAT

SHUGART BONE SPRING NORTH

11. SEC., T., R., M., OR BLK.

AND SURVEY OR AREA

SECTION 30 T18S-R31E

12. COUNTY OR PARISH

EDDY CO.

13. STATE

NM

17. NO. OF ACRES ASSIGNED TO THIS WELL

40

20. ROTARY OR CABLE TOOLS

Rotary

22. APPROX. DATE WORK WILL START\*

As soon as approved

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
5"	Conductor	NA	40'	Cement to surface with Redi-mix
17 1/2"	H-40 13 3/8"	48	450'	450 Sx. circulate to surface
11"	K-55 8 5/8"	32	2800'	710 Sx. circulate to surface
7 7/8"	K-55 5 1/2"	15.5 & 17	8500'	770 Sx. estimate top of cement 2000'

- Drill 25" hole to 40'. Set 40' of 20" conductor and cement to surface with Redi-mix.
- Drill 17 1/2" hole to 450'. Run and set 450' of 13 3/8" 48# H-40 ST&C casing. Cement with 450 Sx. of Class "C" cement + 2% CaCl, circulate cement to surface.
- Drill 11" hole to 2800'. Run and set 2800' of 8 5/8" 32# K-55 ST&C casing. Cement with 710 Sx. of cement as follows: 510 Sx. of 35/65 POZ Class "C" + 12% Salt + 1/4 # flocele/Sx. + 1 # Gilsonite/Sx. + 6% Bentonite, tail in with 200 Sx. of Class "C" + 2% CaCl, circulate cement to surface.
- Drill 7 7/8" hole to 8500'. Run and set 8500' of 5 1/2" casing as follows: 1600' of 5 1/2" 17# K-55 LT&C, 6200' of 5 1/2" 15.5# K-55 LT&C, 700' of 5 1/2" 17# K-55 LT&C casing. Cement with 770 Sx of cement as follows: 200 Sx. of 35/65 POZ + 12% Salt + 1/4 # flocele/Sx. + 1 # Gilsonite/Sx. + 6% Bentonite, tail in with 570 Sx. of (15:68:11) POZ Class "H" CSE + 4.3% Salt + .3% CD-32 + 5# Gilsonite/Sx. + .5% FL-25. Estimate top of cement 2000'.

OVERSPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

SIGNED Joe T. Janice TITLE Agent DATE 08/20/99

This space for Federal or State office use)

PERMIT NO. \_\_\_\_\_ APPROVAL DATE \_\_\_\_\_

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

CONDITIONS OF APPROVAL, IF ANY:

Acting

Assistant Field Office Manager.

Lands and Minerals

OCT 06 1999

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

\*See Instructions On Reverse Side

