		~%».	 Mark and a finite second s		
Form 3160-5 (June 1990)	1990) DEPARTMENT OF THE INTERIOR				FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
BUREAU OF LAND MANAGEMENT					NM-37826-A
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals					6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE					7. If Unit or CA, Agreement Designation
I. Type of Well Oil Well X Well Other					I, Well Name and No.
2. Name of Operator					Box Canyon 34 ATN Fed #1
YATES PETROLEUM CORPORATION (505) 748-1471) 3. Address and Telephone No.					0. API Well No. 30-015-30779
105 South 4th St., Artesia, NM 88210					10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2260' FSL & 660' FEL of Section 34-T20S-R21E (Unit I, NESE)					Wildcat.
2260' FSL & 660	' FEL of Section	n 34-T20S-R21	E (Unit I, NES	E)	
••••••···				<u> </u>	Eddy Co., NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR					, OR OTHER DATA
TYPE OF SU	BMISSIONCEPTED	OR RECORD	ТҮР	E OF ACTION	· · · · · · · · · · · · · · · · · · ·
Notice of Ir	tent		bandonment		Change of Plans
X Subsequent	Report DEC O	n 1337 (m)	lecompletion lugging Back		New Construction
			Casing Repair		Water Shut-Off
(Orig: sgd	"GAHY GOURLE		l iering Casing Muher Intermediate	e casing &	Conversion to Injection Dispose Water
		i `	cement		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Compl give subsurface location	eted Operations (Clearly state all s and measured and true vertical	pertinent details, and give depths for all markers ar	pertinent dates, including estimated zones pertinent to this wo	nated date of starting an	by proposed work. If well is directionally drilled,
TD 1915'. Rea (1920.71') of 1879'. Cement CaCl2 (yield 1 seal and 5#/sa CaCl2 (yield 1 Cement did not 1500'. Ran 1" 11-26-99. WOC CaCl2. PD 1:1 sacks "C" with 910'. Spotted Tagged cement 3/4 hour. Ran PM 11-26-99. 4% CaCl2. PD 140 sacks "C"	ched TD at 4:00 casing set at 19 ed with 200 sack .52, weight 14.6 ck salt (yield 1 .34, weight 14.8 circulate. WOC . Tagged cement 2 hours. Ran 1 5 PM 11-26-99. 3% CaCl2. PD 4 75 sacks "C" wi at 827'. Spotte 1". Tagged cem WOC 3/4 hour. R 11:00 PM 11-26-9 with 4% CaCl2. . Spotted 150 s	PM 11-25-99. 15'. Regular s Thixadd, 1/) and 400 sac .90, weight 1). PD 12:15 5 hours. Ra at 1300'. S ". Tagged ce WOC 2 hours. :00 PM 11-26- th 4% CaC12. d 50 sacks "C ent at 827'. an 1". Tagge 9. WOC 1 hou PD 1:00 AM 11 acks "C" with	Ran 46 joints guide shoe se 4#/sack cellos ks 65-35-6, 5# 2.8). Tailed AM 11-26-99. n Temperature potted 50 sack ment at 1240'. Ran 1". Tagg 99. WOC 3 hou PD 7:30 PM 11 " with 4% CaC1 Spotted 35 sa d cement at 74 r. Ran 1". T -27-99. WOC 1 2% CaC12. PD	of 8-5/8" t at 1915'. eal, 10#/sac /sack gilson in with 200 Bumped plug Survey and s "C" with Spotted 7 ed cement at rs. Ran 1" -26-99. WO 2. PD 8:45 cks "C" with 4'. Spotted agged cemen -1/2 hour. 3:00 PM 11	24# 8rd J-55 ST&C Float collar set at ck gilsonite and 1% nite, 1/4#/sack cello- sacks "C" with 2% to 800 psi, 0K. found top of cement at 1% CaCl2. PD 11:00 AM 5 sacks "C" with 2% t 1071'. Spotted 125 . Tagged cement at C 1 hour. Ran 1". PM 11-26-99. WOC h 4% CaCl2. PD 10:00 d 40 sacks "C" with t at 587'. Spotted Ran 1". Tagged -27-99. Circulated NEXT PAGE: Dec 3, 1999
Approved by		Title	·····		Date
Conditions of approval, if a	· · · · · · · · · · · · · · · · · · ·				

-

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.