

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-37826-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Box Canyon 34 ATN Fed #1

9. API Well No.

30-015-30779

10. Field and Pool, or Exploratory Area

Wildcat

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, conductor, resume
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

drlg, surface casing & cement (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 24" hole with rat hole machine at 12:15 PM 11-17-99. Set 26' of 20" conductor pipe and cemented to surface. NOTE: Notified Don Early w/BLM-Carlsbad of spud. Resumed drilling a 17-1/2" hole with rotary tools at 11:00 AM 11-19-99. Drilled to 263'. Cut a window in 20" conductor and ready-mixed to surface with 16 yards of ready-mix. WOC. Drilled cement and drilled to TD of 341'. Reached TD at 12:30 PM 11-21-99.

Ran 7 joints of 13-3/8" 48# H-40 8rd ST&C (298.20') of casing set at 290'. 1-Texas Pattern notched guide shoe set at 290'. Insert float set at 249'. Cemented with 100 sacks "H", 10% A-10B, 1/4#/sack celloseal, 10#/sack gilsonite and 1% CaCl2 (yield 1.52, weight 14.6) and 150 sacks 65-35-6, 5#/sack gilsonite and 2% CaCl2 (yield 1.93, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 9:00 PM 11-21-99. Circulated 178 sacks to pit. WOC. Cut off and installed rotating head rubber. Drilled out at 6:00 PM 11-22-99. WOC 21 hours. Reduced hole to 12-1/4". Resumed drilling. NOTE: Received verbal permission from Jim Amos w/BLM-Carlsbad to set casing at 290'. Cementing was witnessed by Don Early w/BLM-Carlsbad.

(ORIG. SGD.) GARY GOURLEY

14. I hereby certify that the foregoing is true and correct

Signed

Rusty Klein

Title Operations Technician

Date Dec. 3, 1999

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date