YATES PETROLEUM CORPORATION Whitetail ATW Federal #1 Section 35-T20S-R21E Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

9-8-2000 - Blew well down. Swabbed. Shut well in. 9-9-11-2000 - Loaded tubing with 7% Morrow fluid. Released packer and TOOH. Rigged up wireline. Set CIBP at 7600'. TIH with 4" casing guns and perforated 5964-6156' w/19 .42" holes as follows: 6150-6156', 5976-5980' and 5964-5970' (1 SPF - Cisco). TOOH with casing guns and rigged down wireline. TIH with packer and RBP to 4000'. Shut well in for night. 9-12-2000 - Finished TIH with tools. Set RBP at 6168' and tested to 1000 psi. Set packer at 6124'. Break down perforations. Swabbed. Shut well in. 9-13-2000 - Flow and swab test. Shut well in. 9-14-2000 - Acidized perforations 6150-6156' with 750 gallons of 15% iron control HCL acid. Swabbed and flow tested. Shut well in. 9-15-2000 - Swabbed & flow tested. Loaded tubing. Moved tools and straddle perforations 5964-5980'. Nippled up tree. Tested packer to 1000 psi. Shut well in. 9-16-18-2000 - Acidized perforations 5964-5980' with 1000 gallons of 15% iron control HCL acid. Swabbed & flow tested. Shut well in. 9-19-2000 - Flow tested. Shut well in. Released well to production department.

Operations Technician January 31, 2001