

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTN. M. OIL  
SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)FORM APPROVED  
OMB NO. 1004-0136  
Expires: February 28, 1995

## APPLICATION FOR PERMIT TO DRILL OR DEEPEN

## 1a. TYPE OF WORK

DRILL ☒DEEPEN ☐

## b. TYPE OF WELL

OIL  
WELL ☐GAS  
WELL ☒OTHER ☐SINGLE  
ZONE ☒MULTIPLE  
ZONE ☐

## 2. NAME OF OPERATOR

OCEAN ENERGY, INC. 169355 (SCOTT WEBB) 303-308-8863

## 3. ADDRESS AND TELEPHONE NO.

1670 BROADWAY SUITE 2700 DENVER, COLORADO 80202-4824

## 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface

1800' FEL &amp; 1980' FSL SEC. 21 T18S-R31E EDDY CO. NM

At proposed prod. zone SAME

## 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE\*

Approximately 10 miles Southeast of Loco Hills New Mexico

## 15. DISTANCE FROM PROPOSED\*

LOCATION TO NEAREST

PROPERTY OR LEASE LINE, FT.

(Also to nearest drlg. unit line, if any)

1800'

## 16. NO. OF ACRES IN LEASE

480

## 17. NO. OF ACRES ASSIGNED

TO THIS WELL

320

## 18. DISTANCE FROM PROPOSED LOCATION\*

TO NEAREST WELL, DRILLING, COMPLETED,

OR APPLIED FOR, ON THIS LEASE, FT.

2310'

## 19. PROPOSED DEPTH

12,200'

## 20. ROTARY OR CABLE TOOLS

ROTARY

## 21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3638' GR.

## 22. APPROX. DATE WORK WILL START\*

WHEN APPROVED

23.

## PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	CAPITAN CONTROLLED WATER BASIN
25"	CONDUCTOR 20"	NA	40'	Cement to surface with Redi-mix
17 1/2"	H-40 13 3/8"	48	640' 500' RAZ	450 Sx. Circulate to surface
11"	HCK-55 8 5/8"	32	3000'	860 Sx. " "
7 7/8"	S-95, N-80 5 1/2"	17	12,200'	490 Sx. Estimate top of cement 9700'

1. Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix.

2. Drill 17 1/2" hole to 500'. Run and set 500' of 13 3/8" 48# H-40 ST&amp;C casing. Cement with 450 Sx. of Class "C" cement + 2% CaCl, circulate cement to surface.

3. Drill 11" hole to 3000'. Run and set 3000' of 8 5/8" 32# HCK-55 LT&amp;C casing. Cement with 460 Sx. of Class "C" 35/65 POZ + 6% Gel + 5% Salt, tail in with 400 Sx. of Class "C" cement + 1% CaCl, circulate cement to surface.

4. Drill 7 7/8" hole to 12,200'. Run and set 12,200' of 5 1/2" casing as follows: 2200' of S-95 17# LT&amp;C, 9500' of N-80 17# LT&amp;C, 500' of S-95 17# LT&amp;C. Cement with 300 Sx. of Class "C" 35/65 POZ, tail in with 190 Sx. of 50/50 Class "H" + 10% Salt, + .25% Dispersant, + 2% Gel. Estimate top of cement 9700'

APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED Scott Jonica TITLE AgentDATE 12/19/99

(This space for Federal or State office use)

PERMIT NO. \_\_\_\_\_

APPROVAL DATE \_\_\_\_\_

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
CONDITIONS OF APPROVAL, IF ANY:

Acting

APPROVED BY Earle Smith

TITLE

Assistant Field Office Manager,  
Lands and Minerals

DATE

\*See Instructions On Reverse Side

RECEIVED FOR 1 YEAR

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.