

(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

811 S. 1st Street

Artesia, NM 88210-2894

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

Designation and Serial No.

NM 12212

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reenter a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

type other description or delete

2. Name of Operator

Ocean Energy, Inc. /

3. Address and Telephone No.

1001 Fannin, Suite 1600, Houston, Texas 77002 (713) 265-6834 or 6000

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1800' FEL, Sec. 21, T18S, R31E

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Shugart "21" Federal #1

9. API Well No.

30-015-309086

10. Field and Pool, or Exploratory Area

Shugart-Avalon

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☒ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug back from the Morrow by setting a CIBP @ 11,150' w/46' cmt on top. Set cmt plug from 8559'-8380'.
Perf 6550-54' w/4" sqz gun & sqz. Set cement reainer @ 6500' w/20' cement on top. Perf Avalon perfs 6412-33'
with total of 44 holes. Set 2-3/8" tbg & pkr @ 6464'. Swbd, no show oil or gas. Acidized perf 6412-33 w/1000 gals
7.5% NEFE + additives + 80 1.3 sp fr RCN ball sealers. Swbd made 8 runs, recovering load water, trace of oil. SWI.
Frac'd Avalon perfs 6412-33 via 5-1/2" csg w/170,000 gals 3500 cross link gel. 15000# sand thru perfs when screened
out. Swbd - strong gas during run and after - skim of oil. Well flowed 100% oil for 1 hr, then slugging heads. Well dead
in 2-1/2" hrs. Swbd - recovered load water w/10-15% oil. TP 1000 psi. Left well SI - evaluating.

14. I hereby certify that the foregoing is true and correct

Signed

Title Regulatory Specialist

Date 05/09/01

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 29 2001

ALEXIS C. SWOBODA
PETROLEUM ENGINEER