


District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
2040 South Pacheco
Santa Fe, NM 87505



Form C-101
Revised March 17, 1999

Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address Yates Petroleum Corporation 105 South Fourth Street Artesia, New Mexico 88210		² OGRID Number 025575
³ Property Code 25153	⁴ Property Name Rudolph ATX State	⁵ API Number 30-015-30938
		⁶ Well No. 2

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	16	19-S	31-E		660'	North	990'	West	Eddy

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1 Wildcat Mississippi					¹⁰ Proposed Pool 2 96068				

¹¹ Work Type Code N	¹² Well Type Code G	¹³ Cable/Rotary Rotary	¹⁴ Lease Type Code S	¹⁵ Ground Level Elevation 3483'
¹⁶ Multiple NO	¹⁷ Proposed Depth 12,350'	¹⁸ Formation Mississippi	¹⁹ Contractor Not determined	²⁰ Spud Date ASAP

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17 1/2"	13 3/8"	48 #	550'	450 sx	circulated to surface
12 1/4"	8 5/8"	32 #	3500'	1500 sx	circulated "
7 7/8"	5 1/2"	17 #	12,350'	400 sx	TOC-9500'

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone.

Describe the blowout prevention program, if any. Use additional sheets if necessary.

Yates Petroleum Corporation proposes to drill and test the Mississippi and intermediate formations. Approximately 500' of surface casing will be set and cement circulated. Intermediate casing will be cement circulated. If commercial, production casing will be run and cemented back to approximately 9500', perforated and stimulated as needed for production.

MUD PROGRAM: 0'-550' FW/Spud Mud; 550'-3500' Brine; 3500'-11,000' Cut brine; 11,000' - TD Salt Gel/Starch/Driscap.

BOPE PROGRAM: 5000# BOPE will be installed on 8 5/8" casing and tested daily.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Ken Beardemphl

Printed name:

Ken Beardemphl

Title:

Landman

Date:

January 25, 2000

Phone:

(505) 748-1471

OIL CONSERVATION DIVISION

Approved by:

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

Title:

Approval Date: 1-26-00

Expiration Date: 1-26-01

Conditions of Approval:

Attached ☐