

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer D10, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-015-30938

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
V-4567

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit letter D : 660 Feet From The North Line and 990 Feet From The West Line  
Section 16 Township 19S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3483' GR

7. Lease Name or Unit Agreement Name  
Rudolph ATX State

8. Well No.  
2

9. Pool name or Wildcat  
Wildcat Mississippian (gas)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Ream hole, set conductor, resume drill <input checked="" type="checkbox"/>	Plug back <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  
Reamed 12-1/4" hole to 26" from surface to 40'. Set 40' of 20" conductor pipe and cemented to surface. NOTE: Notified OCD-Artesia answering service of conductor. Resumed drilling a 17-1/2" hole with rotary tools at 6:00 AM 8-21-2000. NOTE: Notified OCD-Artesia answering service of intent to resume drilling.

Drilled to 558' and hole became very crooked. Set a cement plug as follows to redrill to straighten hole: cemented with 600 sacks "C", 1#/sack KCL and 5/10% CFR3 (yield 1.13, weight 16.0). Filled hole to approximately 200'. TOOH & laid down drillpipe. WOC. TIH and tagged cement at 203'. Drilled out cement plug. Redrilled hole.

TD 558'. Reached TD at 12:45 PM 8-24-2000. Ran 13 joints of 13-3/8" 48# H-40 (563') of casing set at 558'. 1-Texas Pattern notched guide shoe set at 557'. Insert float set at 512'. Cemented with 260 sacks Halliburton Lite, 1/4#/sack flocele and 2% CaCl2 (yield 1.94, weight 12.5). Tailed in with 200 sacks Premium Plug and 2% CaCl2 (yield 1.34, weight 12.5).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 13, 2000  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR BOA

NOV 27 2000

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: