

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-015-30996

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
NM 8-9739-19

7. Lease Name or Unit Agreement Name:

SPUR 11 STATE COM

8. Well No.

1

9. Pool name or Wildcat
TURKEY TRACK: MORROW

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-100) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

BELLWETHER EXPLORATION COMPANY

3. Address of Operator

1331 LAMAR, SUITE 1455, HOUSTON, TEXAS 77010-3039

4. Well Location

Unit Letter D : 660 feet from the NORTH line and 660' feet from the WEST line

Section 11 Township 19S Range 29E NMPM County EDDY

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3364'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spudded Well 4/23/00

4/25/00 - 11-3/4" 42# H-40 casing set at 357'. Cemented w/ 260 sx 35:65 LTPO.

Tested to 500 psi - 30 min, ok. WOC 20 hrs. Circ. TOC @ 58'. Pumped 75 sx to top out, no cmt to surface. Put 15 yards ready mix to top out cement to surf. TOC @ Surf.

4/30/00 - 8-5/8" 32# J-55 casing set at 2996'. Cemented w/ 1300 sx 35-65.6 LT.

Tested to 2000 psi - 30 min, ok. WOC 22 hrs. Circ. out 198 sx. at surface. TOC @ Surf.

05/26/00- TD'd Well @ 11,650'.

05/30/00 - 5-1/2" 17# L-80 casing set at 11,650'. Cemented w/ 658 sx 15-61-11.

Tested to 5000 psi - 10 min, ok. Circ. TOC @ 8000' (calculated)

5/31/00 Rig down. Released Rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Nancy K. Gatti TITLE REGULATORY COORDINATOR DATE 07/10/00

Type or print name NANCY K. GATTI

Telephone No. 713-753-1492

(This space for State use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE JUL 19 2000

Conditions of approval, if any: