

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-31011

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
L-2634-3 B-7717-9 B-9379-8

7. Lease Name or Unit Agreement Name:
CHAPS 12 STATE COM

8. Well No.
1

9. Pool name or Wildcat
TURKEY TRACK; MORROW

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3394'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
BELLWETHER EXPLORATION COMPANY

3. Address of Operator
1331 LAMAR, SUITE 1455, HOUSTON, TEXAS 77010-3039

4. Well Location

Unit Letter G : 1650 feet from the NORTH line and 1800 feet from the EAST line

Section 12 Township 19S Range 29E NMPM County EDDY

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Spudded Well 5/26/00

5/28/00 - 11-3/4" 42# H-40 casing set at 336'. Cemented w/ 400 sx Class "C".
Tested to 350 psi - 15 min. ok. WOC 19 hrs. Circ. cement - TOC @ 40'.
Top out with 70 sx. cement to surface. TOC @ surf.

6/3/00 - 8-5/8" 32# K-55 casing set at 3000'. Cemented w/ 1294 sx 35-65 LTPO.
Tested to 1500 psi - 15 min. ok. WOC 21 hrs. Circ. out 198 sx. cement
at surface - TOC at surface.

7/1/00 - TD'd well at 11,768'.

7/03/00 - 5-1/2" 17.0# L-80 casing set at 11,768'. Cemented w/ 887 sx. Class "C".
Circulated. Calculated TOC at 8000'

7/04/00 Rig Down. Released Rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Nancy K. Gatti TITLE REGULATORY COORDINATOR DATE 07/10/00

Type or print name NANCY K. GATTI Telephone No. 713-753-1492

(This space for State use)

APPROVED BY Jim W. Gamm TITLE District Supervisor DATE 10/2000

Conditions of approval, if any: