Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

81	A.	S.	1	S	t		S	tr	6	e	Ţ		-
					_	_	_	_	_	_	4	_	

5. Lease Designation and Serial No.

	Artesia, NM 882° AND REPORTS ON WELLS or to deepen or reentry to a different reserve R PERMIT-" for such proposals	6. If Indian, Allottee or Tribe Name
	N TRIPLICATE	7. If Unit or CA, Agreement Designation
Type of Well Oil Gas		8. Well Name and No.
Well Well Other		Shugart 18 Federa#1
lame of Operator Newbourne Oil Company		9. API Well No.
Address and Telephone No.		30-015-31383
O Box 5270, Hobbs, New Mexico 88241, 50		10. Field and Pool, or Exploratory Area North Shugart Morrow
Location of Well (Footage, Sec., T., R., M., or Survey Desc	cription)	11. County or Parish, State
660'FNL & 760'FEL, Sec.18 T-18S R-31E		Eddy, NM
CHECK APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, REPORT	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTIO)N
Notice of Intent	Abandonment	Change of Plans
House of intent	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Spud, Surf & Interm Csg	Dispose Water (Note: Report results of multiple completion on Wel
directionally drilled, give subsurface locations and meas	ate all pertinet details, and give pertinent dates, including estimated ured and true vertical depths for all markders and zones pertinent to 704'. Ran 704' 13 3/8" csg. Cemented w/ 400 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 104 sks to pit. WOC & te	Lite (12.4 #/g & 1.99 cf/ft)
10/20/00 Drilled 12 1/4" hole to 4518' Ran 9	ured and true vertical deptils for all markders and zones pertilent to	Lite (12.4 #/g & 1.99 cf/ft) st well head to 500 psi. OK
10/20/00 Drilled 12 1/4" hole to 4518' Ran 9	704'. Ran 704' 13 3/8" csg. Cemented w/ 400 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 104 sks to pit. WOC & te 9 5/8" 40# N & J csg to 4518'. Cemented 1200 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 110 sks to pit. WOC & tes	Lite (12.4 #/g & 1.99 cf/ft) st well head to 500 psi. OK Lite (12.7 #/g & 1.98 cf/sk) st BOP to 1500 psi. OK. OOR AON RECEIVED OCD - ARTESIA
10/20/00 Drilled 12 1/4" hole to 4518' Ran 9	704'. Ran 704' 13 3/8" csg. Cemented w/ 400 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 104 sks to pit. WOC & te 9 5/8" 40# N & J csg to 4518'. Cemented 1200 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 110 sks to pit. WOC & tes	Lite (12.4 #/g & 1.99 cf/ft) st well head to 500 psi. OK J Lite (12.7 #/g & 1.98 cf/sk) st BOP to 1500 psi. OK.
directionally drilled, give subsurface locations and meas 10/20/00MI & spud 17 1/2" Hole. Drilled to & tailed w/ 200 sks 'C' w/ 2% CaCl. 10/29/00Drilled 12 1/4" hole to 4518'. Ran 9 & tailed w/ 200 sks 'C' w/ 2% CaCl.	704'. Ran 704' 13 3/8" csg. Cemented w/ 400 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 104 sks to pit. WOC & te 9 5/8" 40# N & J csg to 4518'. Cemented 1200 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 110 sks to pit. WOC & test and the sks to pit. WOC & test and the sks to pit.	Lite (12.4 #/g & 1.99 cf/ft) st well head to 500 psi. OK Lite (12.7 #/g & 1.98 cf/sk) st BOP to 1500 psi. OK. OOG AON RECEIVED OCD - ARTESIA
10/20/00MI & spud 17 1/2" Hole. Drilled to & tailed w/ 200 sks 'C' w/ 2% CaCl. 10/29/00Drilled 12 1/4" hole to 4518'. Ran S & tailed w/ 200 sks 'C' w/ 2% CaCl. 10/29/00Drilled 12 1/4" hole to 4518'. Ran S & tailed w/ 200 sks 'C' w/ 2% CaCl. 11. I hereby certify that the foregoing is true and correct Signed (This space for Federal or State office use)	704'. Ran 704' 13 3/8" csg. Cemented w/ 400 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 104 sks to pit. WOC & te 9 5/8" 40# N & J csg to 4518'. Cemented 1200 sks BJ 2 (14.8 #/g & 1.32 yd). Circl 110 sks to pit. WOC & test and the sks to pit. WOC & test and the sks to pit.	Lite (12.4 #/g & 1.99 cf/ft) st well head to 500 psi. OK Lite (12.7 #/g & 1.98 cf/sk) st BOP to 1500 psi. OK. OOG AON RECEIVED OCD - ARTESIA
10/20/00MI & spud 17 1/2" Hole. Drilled to & tailed w/ 200 sks 'C' w/ 2% CaCl. 10/29/00Drilled 12 1/4" hole to 4518'. Ran 9 & tailed w/ 200 sks 'C' w/ 2% CaCl. 10/29/00Drilled 12 1/4" hole to 4518'. Ran 9 & tailed w/ 200 sks 'C' w/ 2% CaCl. 11. I hereby certify that the foregoing is true and correct Signed (This space for Federal or State office use)	Title N.M. Young District Manager	Lite (12.4 #/g & 1.99 cf/ft) st well head to 500 psi. OK Lite (12.7 #/g & 1.98 cf/sk) st BOP to 1500 psi. OK. OCT AON RECEIVED OCD - ARTESIA Date 10/30/00