

Drilling Plan

for

David H. Arrington Oil & Gas, Inc.'s

Green-Wooley Boogey Federal "5" #1

660' FWL & 2230' FSL (Unit Letter "L")
Section 5, T-19-S, R-24-E, N.M.P.M.
Eddy County, New Mexico

Lease Serial # NM-103591

Surface Formation: Artesia Group of Permian Age

Estimated Tops of Geologic Markers:

San Andres	@	350'
Abo SLTST	@	3690'
Abo Reef	@	3850'
Wolfcamp	@	5100'
Cisco T.	@	6090'
Cisco L.	@	6520'
Canyon	@	7150'
Atoka	@	8190'
Morrow	@	8285'
Mississippi	@	8500'

Estimated Depths to Water, Oil or Gas Formation:

Water	@	200'
Oil	@	6090'
Gas	@	8190'

Proposed Casing Program:

Drilling will begin with a 20" bit to a depth of 40', into which 55# - 16" casing will be set. With a 12 5/8" bit, drilling will continue from 40' to 1250', into which Arrington will cement 32# - 8 5/8" casing. From 1250' to its total depth of 8,600', Arrington will utilize a 7 7/8" bit, into which 17# - 5 1/2" casing will eventually be cemented.

The surface and production casing strings will be tested to 1000 psi.