Form 3160-5 (August 1999)	UNITED STATES DEPAR .NT OF THE INTERIOR BUREAU OF LAND MANAGEMENT			FORM APF OMB No. 10 OII CONS. Expires Novemi N.M. DIV-DIStea 2 Serial No.				004-0135 C	
al	SUNDRY NOTICES Do not use this form for bandoned well. Use For	AND REPORTS ON proposals to drill or to m 3160-3 (APD) for suc		01 W. G	rand Av				
	IN TRIPLICATE - 0	ther Instructions of	n rovorso s	ide a har	7. lf L	Jnit or CA/	Agreement, Name	and/or No.	
1. Type of Well					8. We	II Name a	nd No.	<u> </u>	
X Oil Well	Gas Well	Other	1.81 17	Ŧ	Dom	nino AC	J Federal #5		
2. Name of Operator / Yates Petroleum Corporation				COP HISTOR		PI Well N			
3a Address 3b. Phone No. 105 S. 4th Street - Artesia, NM 88210 505-748-1			le area code) ()	ARTESIA	10. Fi	eld and Po	ool, or Exploratory	Area	
4. Location of Well (Footage, Sec., T.,R., M., or Survey Description)					S Wild	icat Mis	sissippian	<u></u>	
990' FNL and 990' FEL S	ection 8 T19S R31E					ounty or P	arish, State		
						y Coun			
12. CHECK A	PPROPRIATE BOX(ES	b) TO INDICATE NAT		F ACTION	I, OR OTH		<u>A</u>		
Notice of Intent	Acidize	Deepen		(Start/Resume)	Water	r Shut-Off			
X Subsequent Report	Alter Casing	Fracture Treat	Reclamatio	Well I	ntegrity				
Final Abandonment Notice	Casing Repair	New Construction	Recomplete	Э	XOther		Commence I	Drilling	
	Change Plans	Plug and Abandon	Temporarily Abandon						
	Convert to Injection	Plug Back	Water Disp						
4/19/01 - Spud 26" condu 4/25/01 - Resumed drillin 4/26/01 - TD of 17-1/2" ho Texas Pattern guide shoe Celloflake + 1% CaCl2 (y Bumped plug to 150 psi, 4/27/01 - Drilled out at 10 5/1/01 - TD 12-1/4" hole a Regular guide shoe set a 1/4 pps Celloflake (yld 2.0 Bumped plug to 1400 psi 5/2/01 - Drilled out at 8:00 5/3 - 5/29/01 - Drilling.	ew interval, a Form 3160-4 shall b d, and the operator has determined totor hole at 9:30 AM. Set g with rotary tool at 3:30 P ole at 540' at 8:45 AM. Ra e set at 540'. Insert float s yld 2.01, wt 12.4). Tailed i held OK. Circ 185 sxs. b:30 AM. WOC 20-1/2 hrs at 5:15 AM. Ran 80 jts. (3 t 3395'. Float collar set at 06, wt 12.4). Tailed in with	e filed once testing has been con that the site is ready for final in: 40' of 20" conductor pip M. In 12 jts. (544.73') 13-3/8 et at 492.94'. Cemented n with 200 sxs Class C + Reduced hole to 12-1/- 397.68') 8-5/8" 32# J-55 3355.44'. Cemented with 200 sxs Class C + 1% uced hole to 7-7/8" and r	npleted. Final Aban specition.) e. Notified Jim 3" 48# H-40 cas d with 350 sxs c 2% CaCl2 (yld 4" and resumed casing set at 3 th 1300 sxs BJ CaCl2 (yld 1.34 esumed drilling	donment Notices sh Amos with Ca sing set at 540' dass C 35:65 lif d 1.34, wt 14.8 d drilling. 395'. Lite 35:65:6 + 4, wt 14.8). PD	nall be filed only at rIsbad BLM o te + 5 pps Gil) PD 2:00 PN 3 pps salt + 5	fter all requ f operation sonite + M.	irements, including ons. 1/4 pps		
I hereby certify that the foregoing	is true and correct							<u> </u>	
Name (Printed/Typed) Suşan Herpin			Title Engineering Technician						
Signature Marin Hu			Date	tember 1	12.201	01			
	TED FOR RECUR	SPACE FOR FEDE	RAL OR ST	ATE OFFIC				· · · · · · · · · · · · · · · · · · ·	
ACCEPTED FOR RECORD			Title				Date		
Conditions of approval, if any, and the applicant notics legal or equiti applicant to conduct operations th	Office	u			<u> </u>				
	Marker 1945, OBerlight S212, mak Schlatori St. 15 Shighist Frillin		ingly and willfully to	make to any depart	ment or agency of	i the United	i States any faise, fictr	tious	