State of New Mexico Submit 3 Copies to Appropriate Form C-103 District Office Energy, Minerals and Natural Resources Revised March 25, 1999 DISTRICT WELL API NO. 1625 n. French Dr., Hobbs, NM 88240 DISTRICT II OIL CONSERVATION DIVISION 30-015-31771 811 South First, Artesia, NM 88210 Indicate Type of Lease 2040 South Pacheco DISTRICT III STATE X FEE Santa Fe, NM 875/08 1000 Rio Brazos Rd., Aztec, NM 87410 State Oil & Gas Lease No. DISTRICT IV 2040 S. Pacheco, Santa Fe, NM 87505 648 SUNDRY NOTICES AND REPORTS ON WELL 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS) Turkey Track "11" State Type of Well: Oil Well Gas Well Other Name of Operator Well No. Louis Dreyfus Natural Gas Corp. Address of Operator Pool name or Wildcat 14000 Quail Springs Parkway - Suite 600 - Oklahoma City, OK 73134 Palmillo; Bone Springs, SW Well Location Unit letter 2310' feet from the North line and 1650' feet from the West line. **19S** 28E Section Township Range **NMPM** Eddy County 10. Elevation (Show whether DR, RKB, RT, Gr, etc.) 3458 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND **ABANDONMENT PULL OR ALTER CASING** MULTIPLE CASING TEST AND CEMENT JOB X COMPLETION OTHER: OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propropsed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/5/01 spud well. 6/06/01 ran 10 jts 13 3/8", 48# csg, set at 423', cemented lead w/175 sks 35:65 Poz "C", tailed w/195 sks Class C, circulated 68 sk to reserve. Plug down at 20:00 hrs. Wait on cement 21 hrs., commenced drilling. 6/11/01 ran 66 jts 8 5/8", 32# csq, set at 2798', cemented lead w/710 sks 50:50 Poz Class "C", tailed w/345 sks Class "C", plug down @ 2:35 p.m., circulated 100 sks cement to reserve, float held. Wait on cement 18 1/2 hrs., commenced drilling. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Regulatory Technician 06/19/01 DATE Type or print name Carla Christian Telephone No. 405-749-5263 (This space for State use) DATE 2 6 2001 ORIGINAL SIGNED BY TIM W. GUM APPROVED BY DISTRICT II SUPERVICENTLE

Conditions of approval, if any: