

TIMBISH/SHARP DRILLING

B.O.P. Equipment Intended for use on Rig # 24 + 22

Well To Be drilled for Timb/Sharp

- * All B.O.P equipment is H2S Trim *
- * All Accumulators are Koomey Type-80 : Dual Power Electric/Air *
- * Choke Manifold: * See sheet 2
- 4" Valves : Cameron F/FC, Shaffer DB Hydraulic
- 2" Check Valve: Cameron Type R
- 2" Valves : Cameron or Shaffer

Annular Shaffer Type: Spherical

Annular PSI: 3000

(If Shaffer: Spherical , If Hydril: Type GK)

BOP Type Shaffer LWS

(If Shaffer: LWS or SL, If Cameron: Type U)


BOP Size: 13 5/8 " - 5000 PSI

Rotating Head Type Smith

Rot-Head Furnished By Timb

Rams in top gate: 4 1/2 pipe

Rams in bottom: Blinds



Side Outlets used:

Bottom X Top

4" Valves on Tee

B.O.P. Equipment Intended for use on Rig # 24 + 22

Well To Be drilled for Timb/Sharp

* All Valves (H2S) *

Choke Manifold:

Pressure Rating 3,000 or 5,000 (as Req.)

1 - 4" Valves

2 - 2" Valves

2 - 2" Adjustable Chokes

Valve Types Used:

Cameron - F or FC

Shaffer - B Floseal

WKM type 2

Chokes - Cameron H2 or TC unbolt




EXHIBIT "E"
CHI OPERATING, INC.
Wizard Federal Com., Well No. 2
BOP Specifications