

Attachment to Exhibit "E"
NOTES REGARDING BLOWOUT PREVENTERS
Devon SFS Operating, Inc.
Strawberry "7" Federal Com., Well No. 1
660' FNL & 1750' FWL, Sec. 7-T19S-R31E
Eddy County, New Mexico

1. Drilling nipple will be constructed so it can be removed mechanically without the aid of a welder. The minimum diameter will equal BOP bore.
2. Wear ring will be properly installed in head.
3. Blowout preventer and all associated fittings will be in operable condition to withstand a minimum 3000 psi working while drilling below the 13 3/8" casing and 5000 psi WP while drilling below the 8 5/8" casing.
4. All fittings will be flanged.
5. All full bore safety valve tested to a minimum 5000 psi WP with proper thread connections will be available on the rotary rig floor at all times.
6. All choke lines will be anchored to prevent movement.
7. All BOP equipment will be equal to or larger in bore than the internal diameter of the last casing string.
8. Will maintain a kelly cock attached to the kelly.
9. Hand wheels and wrenches will be properly installed and tested for safe operation.
10. Hydraulic floor control for blowout preventer will be located as near in proximity to driller's controls as possible.
11. All BOP equipment will meet API standards and include a minimum 40-gallon accumulator having two independent means of power to initiate closing operation.