Form 3160-5 (November 1994)

1. Type of Well Oil Well 2. Name of Operator

3a. Address

4. Location of Well (Foo 990 FNL 1980

IITED STATES DEPARTMENT OF THE INTERIOR DIDEALIOET AND MANAGEMENT

C1512 FORM APPROVED Budget Bureau No. 1004-0135

Expires July 31, 1996

SUNDRY NOTICES Do not use this form for abandoned well. Use For	proposals to drill or t	N WELLS Artes o re-enter an	ia, NM 8	AVOPER ial No. 8210 NM66437 6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on 1992 50 side				7. If Unit or CA/Agreement, Name and/or No.	
Type of Well Oil Gas X Other Name of Operator OXY USA WIP Limited Partnership	, 2223 , 2223	★ 500 1	Dry Hole	8. Well Name and No. OXY Boot Jack 1 Federal	
Address P.O. Box 50250, Midland, TX 79710-0250 Location of Well (Footage, Sec., T., R., M., or Survey Description) 990 FNL 1980 FEL NWNE(2) Sec 6 T19S R31E			9. API Well No. 30-015-31925 10. Field and Pool, or Exploratory Area Hackberry Morrow, N.		
990 FRL 1980 FEL NWRE(2) Sec 6 1195 RSIE				11. County or Parish, State Eddy NM	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION		TYF	PE OF ACTION		
X Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production Reclamatio Recomplete Temporaril Water Disp	e Other	
Describe Proposed or Coommpleted Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.					

13. Describe Propose If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

TD - 12340'

PBTD - 11925'

PERFS - 11809-11859'

CASING: 13-3/8" 48# @ 660', 17-1/2", cmt w/523sx, TOC-Circ

9-5/8" 36# @ 3635', 12-1/4", cmt w/1400sx, TOC-Circ

5-1/2" 17# @ 12340', 8-3/4", cmt w/1470sx, TOC-4830'-CBL

- RIH & set CIBP @ 11759', dump 5sx TO 11724'
- M&P 25sx cmt @ 11250-11150'
- M&P 25sx cmt @ 10900-10800'
- M&P 25sx cmt @ 9950-9850'
- 5. M&P 25sox cont @ 6850-6750'
- Cut & pull 5-1/2" csg at approximately 4850'
- M&P 60sx cmt @ 4900-4800'
- 8. M&P 75sx cmt @ 3685-3585'
- 9. M&P 50sox comt @ 3100-3000'
- 10. M&P 50sox comt @ 710-610'
- 11. M&P 20sx cmt Surface Plug

10# MLF BETWEEN PLUGS

 I hereby certify that the foregoing is true and correct Name (PrintedTyped) 	Title
David Stewart	Sr. Regulatory Analyst
lu Stat	Date 3(20(02

THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
Approved by (ORIG. SGD.) ALEXIS C. SWOBODA	Title ETROLEUM ENGINEER	Date MAR 2 5 2002					
Conditions of approval, if any, are attached. Approval of this notice does not warrant or ertify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office						
Fitle 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully	to make to any department or agency of the Un	ited States any false, fictitious or					

fraudulent statements or representations as to any matter within its jurisdiction.

OXY USA WTP LP OXY BOOTJACK FEDERAL #1 SEC 6 T19S R31E EDDY NM

0.0 - 50.0' CEMENT PLUG 20sx 0.0 - 660.0' 17-1/2" OD HOLE 0.0 - 660.0 CEMENT 523sx-CRC 610.0 - 710.0' CEMENT PLUG 50sx 0.0 - 660.0' 13-3/8" OD SURF CSG 660.0 - 3635.0' 12-1/4" OD HOLE 3000.0 - 3100.0' CEMENT PLUG 50sx 0.0 - 3635.0' CEMENT 1400sx-CIRC 0.0 - 3635.0' 9-5/8" OD INT CSG 3585.0 - 3685.0' CEMENT PLUG 75sx 3635.0 - 3685.0' CEMENT PLUG 4750.0 - 4850.0' CEMENT PLUG 60sx 4800.0 - 4850.0' CEMENT PLUG 6750.0 - 6850.0' CEMENT PLUG 25sx 3635.0 - 12340.0' 8-3/4" OD HOLE 4830.0 - 12340.0' CÉMENT 1470sx-CBL 4800.0 - 12340.0' 5-1/2" OD PROD CSG 9850.0 - 9950.0' CEMENT PLUG 25sx 10800.0 - 10900.0' CEMENT PLUG 25sx 11150.0 - 11250.0' CEMENT PLUG 25sx 11724.0 - 11759.0' CEMENT PLUG 5sx 11809.0 - 11900.0' ABANDONED PERFS 11759.0 - 11759.0' CIBP 11925.0 - 11950.0' CEMENT PLUG 3sx 11960.0 - 11988.0' ABANDONED PERES 125.0 - 11950.0 Graph 12/4/401:6 WW 12 3002 12091.0 - 12101.0' ABANDONED PERES [™] 360,∄D: 12340′