(July 1992)	ITED STATES NO. COLDER I CELIONE ON APPROVED ST					
A.,	DEPARTh	Expires: E-1 1004-0136				
BUREAU OF LAND MANAGEMENT					5. LEASE DESIGNATION AND SERIAL NO. LC-029387-B	
APPLICATION FOR PERMIT TO DRILL OR DEEPEN					6. IF INDIAN, ALLOTTER OR TRIBE NAME	
b. TIPE OF WELL					7. UNIT ACREEMENT NAME	
WELL	WELL X OTHER	<u> </u>		ONE	S. FARM OR LEASE NAME WELL NO.	
					WEST SHUGART "30" FED. # 6	
110 WEST LOUISTANA CUTTE (10 NEED						
At surface with any State requirements.*)						
					11. BEC., T., E., M., OR BLX. AND SUEVEY OF AREA	
14. DISTANCE IN MILES AND DIRECTION FROM NEARING TOTAL OF THE STATE OF						
Approximately 8 miles Southeast of Loco Hills Now Movies						
LOCATION TO NIAREST 15. NO. OF ACRES IN LEASE 17. NO. OF					EDDY CO NEW MEXICO	
13. DISTINCT FROM PROPERTY (4/0				TOTH	is well Ro 311	
TO NEAREST WELL, DRILLING, COMPLETED. OR AFFLIED FOR, ON THIS LEASE, FT. 530' 21. ELEVATIONS (Show whether DF, RT, GR, etc.)		E o o t	19. FROPOSED DEPTH 20. ROTAL 12,400' ROTA		RY	
3578' GR. 22. APPROL DATE WORK WILL START.						
PROPOSED CASING AND GENENTING BROOM						
SIZE OF HOLE GRADE SIZE OF CASING WEIGHT PER FOOT				Capit	an Controlled Water Basin	
25"	Conductor	NA	40'	Cement t	QUANTITY OF CEMENT	
17 ¹ / ₂ "	<u>H-40 13 3/8"</u>	48	775'	800 Sx.	circulate to surface	
7 7/8"	J-55 8 5/8"	32	2800'		1000 Sx. " " "	
	N-80 5 ¹ / ₂ "	17	12,400'	1250 Sx.	Estimate TOC 2600'	
 Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix. Drill 17¹/₂" hole to 775'. Run and set 775' of 13 3/8" 48# H-40 ST&C casing. Cement with 800 Sx. of Class "C" cement + 2% CaCl + ¹/₄# of Flocele/Sx. circulate cement to surface. Drill 12¹/₄" hole to 2800'. Run and set 2800' of 8 5/8" 32# ST&C casing. CEment with 750 Sx. of Class "C" Light cement + additives, tail in with 250 Sx. of Class "C" cement + 25 CaCl, + ¹/₄# Flocele/Sx. circulate cement to surface. Drill 7 7/8" hole to 12,400'. Run and set 12,400' of 5¹/₂" as follows: 2200' of 5¹/₂" S-95 17# LT&C, 9100' of 5¹/₂" 17# N-80 LT&C, 1100' of 5¹/₂" 17# N-80 Buttress thread. Cement in 2 stages. additives, cement 2nd stage with 600 Sx. of Class "H" Super Premium Plus + 						
additives. cement 2nd stage with 450 Sx. of Class "H" Super Premium Plus + 250 Sx. of Class "C" + 2% CaCl + ½# Flocele/Sx. Estimate top of cement 2500'. IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.						
signed are	-0	•	gent	nter program il any.	07/19/01	
(This space for Federal	or State office use)				DATE	
PURATE NO.	V	293031-1234	ADVAL DATE	PPROVAL	SUBJECT TO	
	Martant or certify that the applic ANY:	RECEIVE	to the rights in the subject	BENERAL R PECIAL'ST	EQUIREMENTS AND	
APPROVED BY	SLIE A. THE			DATE	OCT 0 1 2001	
		*See Instructions Q	Reverse Side	APPROV	AL FOR 1 YEAR	

Title 18 U.S.C. Section 1001, makes it a crime for any performing war willfully to make to any department or agency of the United States any false fictilious of formula of the United States any false fictilious of formula of the United States any false fictilious of formula of the United States any false fictilious of formula of the United States and willfully to make to any department or agency of the



4 · · ·

ب د

10.02 Mr. 502