



State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other	WELL API NO. 30-015-32205
2. Name of Operator KUKUI OPERATING COMPANY (LARRY STRIDER 915-687-6200)	5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
3. Address of Operator 203 WEST WALL SUITE 810 MIDLAND, TEXAS 79701	6. State Oil & Gas Lease No. V-5072
4. Well Location Unit Letter A : 660' feet from the North line and 660' feet from the EAST line Section 36 Township 19S Range 21E NMPM County EDDY CO.	7. Lease Name or Unit Agreement Name: POKEY "BAK" STATE
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 4208' GR.	8. Well No. 1
	9. Pool name or Wildcat UNDES. BUNTING

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: Change casing & cementing ☐

SUBSEQUENT REPORT OF:

- REMEDIATION WORK ☐ ALTERING CASING ☐  
COMMENCE NOTIFY OCD SPUD & TIME  
CASING TEST TO WITNESS CEMENTING OF  
CEMENT JO ALL CASING STRING  
OTHER: 9 5/8 "

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Drill 20" hole to 40'. Set 40' of 14" conductor pipe and cement to surface with Redi-mix.

\* 2. Air drill 12 1/4" hole to 1450'. Run and set 1450' of 9 5/8" 36# J-55 ST&C casing. Cement with 720ft<sup>3</sup> of 9.0#/Gal Class "C" foam cement (1150' of fill + 100% excess), tail in with 188ft<sup>3</sup> (300' of fill + 100% excess) of Class "C" cement + 2% CaCl. If cement does not circulate, immediately cement annulus through 13 5/8" casing head with an additional 200ft<sup>3</sup> of 9#/Gal Class "C" foam cement and cap with 50 Sx. of Class "C" cement + 2% CaCl.

3. Drill 8 3/4" hole to 8150'. Run and set 8150' of 5 1/2" 17# N-80 LT&C casing. Cement with 1000 Sx. of 50/50 POZ Class "C" cement + additives, estimate top of cement 4700' from surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Joe T. Janica TITLE Agent DATE 04/11/02

Type or print name Joe T. Janica Telephone No. \_\_\_\_\_

(This space for State use)

APPROVED BY Jim W. Brown TITLE District Supervisor DATE APR 17 2002

Conditions of approval, if any: If cement does not circ to surface, operator to run 1" Log.

\* Casing to be perforated, squeezed in areas where cement is absent. 'ACE'