


(SUBMIT IN TRIPLICATE)

Land Office Las Cruces
Lease No. LC 064850
Unit East Texas HillUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Subsequent report of plugging and</u> <u>abandoning</u> X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

East Texas Hill Unit No. 1

Hobbs, New Mexico January 20, 1954

Well No. 1 is located 660 ft. from NE line and 650 ft. from E line of sec. 1
SE SW/4 Section 1 22-5 21-5 NMPH
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Ledy New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4573 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Subject well was drilled to total depth 10,596', Ellenburger formation, without encountering commercial production. In accordance with our Notice of Intention dated January 4, 1954, well was plugged and abandoned in the following manner:

1. From 10,596-10,410', Ellenburger formation, used 78 sacks cement.
2. From 9,960-10,060', Montoya formation, used 42 sacks cement.
3. From 9,387-9,487', Devonian formation, used 42 sacks cement.
4. From 8,700-8,850', Pennsylvanian Sand formation, used 63 sacks cement.
5. From 4,614-5,714', Wolfcamp formation, used 42 sacks cement.
6. From 3,500-3,600', Abc formation, used 42 sacks cement.
7. From 1,910-2,010', Base of 9 5/8" casing, used 42 sacks cement.
8. From 0-50', Top 50' of hole, used 17 sacks cement.

In all other intervals 12# mud was used, and suitable steel marker was set in cement at surface and location was restored to its original condition.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company
 Address Box 427
Hobbs, New Mexico
 By _____
 Title District Superintendent