

Ralph Lowe No. 1 Indian Basin

Page 3

9/24/62

Pumped a total of 696 bbls of 8.6 mud & wtr in hole. Opened tbg to pit, got back 30 bbls. Fluid equalized. Pulled pkr loose. Circ gas out. Pulled out of hole. Put on new bit & Baker scraper, went in hole, drid bridge plug at 7550'.

9/25/62

Drid retainer at 7615' & cement down to 7690'. Picked up 48 jts of tbg. Went down to 9350'. Circ hole clean. Pulled out of hole. Rig up Western. Ran gauge ring, hung up at 3260'. Lost same. Picked up overshot & jars, went in hole to 9372'. Circ 3 hrs.

9/26/62

Pulled out of hole with fish. Ran gauge ring by Western Co. Set Baker Model D production pkr at 8980', center of pkr. Set Baker Model D production pkr at 7640', top of pkr.

9/27/62

Went in hole with 2-7/8" tbg. Circ at 7550'. Picked up 2-3/8" tbg buttress in mouse hole & stood in derrick.

9/28/62

Laid down 2-7/8" tbg. Picked up 5' guide & 16' 75" Baker seal assembly to set in Model D at 8980' - 1340' up. Put 3' seal assembly at 7640' - 315' up. Baker Model K Double Grip Snap Set Dual Packer set at 7324' - 78'. Spaced out string with 10' - 8' - 4' - 2' perf jets one jt from top. 1'-87" change over nipple on top. Displaced mud with water. Set same down on head. No seating nipple in string. Put Baker snap latch assembly on bottom of short string 2-3/8" tbg buttress. One ft. seating nipple one jt. from bottom. Went in hole, landed same in Model K at 7325'. Spaced out string with 3-8' perf jets 2 of same J-55, one jt. from top. 1'-87" change over nipple on top, set same on hanger.

9/29/62

Set rotary table & BOP off. Set tbg head on & flanged up well. Rigged up Western Co. Perf 4 jets/ft with link jets thru 2-3/8" tbg.

From 9039' - 9049'	10'	)	
9199' - 9207'	8'	)	
9227' - 9233'	8'	)	46'
9238' - 9246'	8'	)	
9251' - 9263'	12'	)	

Swbd down well to 7650'. Showed a little gas.

9/30/62

By Schlumberger: Re-perf 9227' - 9263' with link jets. 4 jets/ft. Went in hole to perf 9199' - 9207'. Shot did not go off, lost 4-1/2 ft. of link jet in hole at 5071'.

By McCullough: Dumped 35 gals 20% acid with 1-3/4" dump bailer on fish at 5071'.

9/2  
F  
de  
100

9/2  
S  
P