

R. E. O. C. C. COPY

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS 1952

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	. x
TO FULL OR ALTER CASING	ХХ	SUBSEQUENT REPORT OF ABANDONMENT. SUPPLEMENTARY WELL HISTORY.	

	/	***************************************	June 15		, 19 62
Well No. 1-X is loca	ated 624 ft. fr	$\operatorname{com}_{-} \left\{ \begin{array}{l} XXXX \\ S \end{array} \right\}$ line and	624 ft. fro	m {XXX line of sec.	8
SW/4 Sec. 8 (1/4 Sec. and Sec. No.)	21-S (Twp.)	23-E (Range)	NMPN (Meridian)		
Wildcat (Field)	Eddy	nty or Subdivision)		New Mexico	

The elevation of the derrick floor above sea level is 4046 ft.

DETAILS OF WORK

ctive sands; show sizes, weights, and lengths of prop ing points, and all other important proposed work)

Spudded: 3-29-62

Conductor String: 76'

Liner String: 7529'

Surface String: 757**1** Intermediate String: 5492'

7102-39', 7209-39', 7454-7475'. Perf:

Selectively treated as follows:

7102-391

5-24-62-10,000 gals acid. Swbd dry.

5-26-62-Squeezed cmtd w/150 sks reg neat, 4500# - WOC 24 hrs.

Press tested w/3000# --held O.K.

7209-391 5-29-62-5,000 gals acid. Swbd dry.

7454'-7475' 5-28-62- 4,000 gals acid. Swbd dry. 5-31-62: Ran csg cutter. Cut & rec 835' 7" csg. Ran tbg & set cmt plugs as

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. follows: 30 sks @ 7490; 25 sks @ 5450; 30 sks @ 950; 20 sks @ surf. (See be-Company Odessa Natural Gasoline Co., Agent for Standard Oil Co. of Texas-low)

Address Box 3908	
Odessa, Texas	By D. N. Dunnavant
	L. N. Dunnavant

*Will P & A at 3:00 A.M. on Mm 6-1-62.

Title Production Superintendent

GPO 862040