

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE
(Other in- long on to
verse side)Form approved
Project Bureau No. 41-1142
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

600 FNL & 830 FEL Sec 4-215-25E

Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

Convert to water disposal ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

It is proposed to convert this well to water disposal by the following procedure:

Set 45% cement plug 10,132'-9800'. Squeeze 10% cement into formation at 9600'. Plug 20 holes 8300-8400 (to be determined). Spot 15% LSTN acid across perf. with thg at 8250'; spot fresh water mixed w/ 25 gals Unitol Chem FH 386, 10# sodium sulfide, 10 gal potassium hydroxide / 100 gal in annulus as packed fluid. Pump 200 bbl down annulus. Break & test perf w/ 2600 gal 15% LSTN acid at 5 BPM with ball sealers. Flush w/ produced water. Place on injection.

See NM O.C.C. Case # 4284 Order # R-3916

18. I hereby certify that the foregoing is true and correct

SIGNED

M. E. York

TITLE Adm. Section Chief

DATE

4-2-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

MAY 15 1970

USGS-5

FILE

Art

*See Instructions on Reverse Side

O. C. C.
ARTESIA, OFFICE