

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87504
APR 23 1993

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Barber Oil, Inc.	8. Farm or Lease Name L. F. Rayroux
3. Address of Operator P. O. Box 1658 Carlsbad, NM 88221-1658 (505) 887-2566	9. Well No. 1-A
4. Location of Well UNIT LETTER H 1950 FEET FROM THE North LINE AND 630 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 21S RANGE 26E NMPM.	10. Field and Pool, or Wildcat Carlsbad Delaware
15. Elevation (Show whether DF, RT, GR, etc.) 3165' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Within 90 days of approval will MOL, rig up pulling unit, remove rods and tubing. Spot 100' of cement from T.D. to $\pm 2572'$ or 62' above the uppermost perforation at 2634' and tag. Fill 5 1/2" with 9# mud to $\pm 755'$. Spot cement in 5 1/2" csg across 8-5/8" csg shoe such that plug extends 50' above and below csg shoe or from 755' to $\pm 655'$. Fill remaining 5 1/2" csg to within 50' of surface with 9.0# mud. Fill 5 1/2" AND 8-5/8" X 5 1/2" annulus AND 8-5/8" X 10-3/4" annulus from 50' to the surface with cement and set marker.

Relevant Particulars: 10-3/4", 40# cemented w/ 75 sxs
8-5/8", 28# cemented w/ 50 sxs
5 1/2", 14# cemented w/ 100 sxs
Top of oil zone 2634'
Perfs from 2634' to 2642' (8')
T.D. 2672'
Well spudded 5/3/55. Completed 6/24/55.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michael J. Ruiz TITLE President DATE 4/21/93
APPROVED BY Ronald W. [Signature] TITLE _____ DATE _____