NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

| | Indicate Nature of Notice by Checking Below | | | |
|--|--|--|---------|--|
| Notice of Intention to Change Plans | Notice of Intention to Temporarily Abandon Well | Notice of Intention to Drill Deeper | | |
| Notice of Intention to Plug Well | Notice of Intention to Plug Back | Notice of Intention to Set Liner | | |
| Notice of Intention to Squeeze | Notice of Intention to Acidize | Notice of Intention to Shoot (Nitro) | | |
| Notice of Intention to Gun Perforate | Notice of Intention (Other) | Notice of Intention (Other) | | |
| OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO | N (Owell, Now F | evico July | 8, 1954 | |
| Gentlemen: | | | | |
| | to do certain work as described below at the | | | |
| John M. Kelly | Moliilan 136 - 205 , 250 , 1 | Well Noin | J - | |
| NW / (Company or Ope | ")6 ~ _ 205 | 311doat | (Unit) | |
| (40-acre Subdivision) | , I, I | WIFM., | P00 | |
| | total depth of 11,560 f | | | |
| Will set cement plug 25 anx at 11,400 25 anx at 10,200 25 anx at 1,700 25 anx in 8 5/5 | | | 1. | |
| Will set cement plug 25 anx at 11,400 25 anx at 10,200 25 anx at 1,700 25 sax in 8 5/9° Fill with heavy aud | gs as follows: Oft. Oft. Oft. casing at 410 ft. between plugs and leave | a 3 5/8" casing in well | 1. | |
| Will set cement plug 25 anx at 11,400 25 anx at 10,200 25 anx at 1,700 25 anx in 8 5/9 Fill with heavy aud | oft. oft. oft. oft. oft. being at 410 ft. between plugs and leave | | 1. | |
| Approved App | oft. oft. oft. oft. coung at 410 ft. between plugs and leave | 3 5/8" casing in well | 7 | |
| Will set cement plug 25 sex at 11,400 25 sex at 10,200 25 sex at 1,700 25 sex in 8 5/5° Fill with heavy sud Approved | oft. oft. oft. oft. coung at 410 ft. between plugs and leave | Ohr Relly Company or Operator Company or Operator | 7 | |
| Approved Approved Approved Approved Approved Approved | oft. oft. oft. oft. coung at 410 ft. between plugs and leave | ohn M Kelly Company or Operator Operator | to: | |