

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Jenkins & McQueen

(Company or Operator)

Yarbro

(Lease)

Well No. **1**, in **NW** $\frac{1}{4}$ of **NE** $\frac{1}{4}$, of Sec. **25**, T. **22 S**, R. **26 E**, NMPM.

Wildcat

Pool,

Eddy

County.

Well is **990** feet from **north** line and **1,650** feet from **east** lineof Section **25**. If State Land the Oil and Gas Lease No. isDrilling Commenced **September 17**, 19 **52**. Drilling was Completed **October 29**, 19 **52**Name of Drilling Contractor **Jenkins & McQueen**Address **1009 Coleord Building, Oklahoma City, Oklahoma**Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until
19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **425'** to **475'** feet.No. 2, from **1991** to **2059** feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
12-1/2"	50	used	46'		46'		Drilling string
10-3/4"	40	"	112		112		" "
8-5/8"	28	"	400		400		" "
5-1/2"	14	"	2123		2123		" "

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

DRY HOLE

Result of Production Stimulation

Depth Cleaned Out

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto:

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from.....feet to **2255**.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing.....**Dry Hole**....., 19.....

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy..... 401	T. Devonian.....	T. Ojo Alamo.....	
T. Salt..... 1115	T. Silurian.....	T. Kirtland-Fruitland.....	
B. Salt..... 1335	T. Montoya.....	T. Farmington.....	
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....	
T. 7 Rivers.....	T. McKee.....	T. Menefee.....	
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....	
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....	
T. San Andres.....	T. Granite.....	T. Dakota.....	
T. Glorieta.....	T.	T. Morrison.....	
T. Drinkard.....	T.	T. Penn.....	
T. Tubbs.....	T.	T.	
T. Abo.....	T.	T.	
T. Penn.....	T.	T.	
T. Miss.....	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	105	105	Gravel	1655	1690	35	Anhydrite & Lime
105	230	125	Red Rock	1690	1725	35	Brown Lime
230	240	10	Lime	1725	1860	35	Anhydrite & Lime
240	245	5	Red Sand	1760	1782	22	Anhydrite
245	300	55	Red Rock	1782	1794	12	Black Lime
300	345	45	Red Rock & Shells	1794	1800	6	Bray Sandy Lime
345	398	53	Red Rock	1800	1820	20	Lime
398	401	3	Potash & Shells	1820	1830	10	Blue Shale
401	890	489	Anhydrite	1830	1865	35	Gray Sandy Lime
890	935	45	Anhydrite & Gyp	1865	1988	123	Lime
935	1115	180	Anhydrite	1988	2026	38	Sand
1115	1335	220	Salt	2026	2035	9	Blue Sand & Blue Shale
1335	1354	19	Anhydrite	2035	2059	24	Sand & Shale
1354	1365	11	Brown Lime	2059	2098	11	Blue Sandy Shale
1365	1385	20	Lime & Shells	2070	2125	55	Sand & Shale
1385	1410	25	Lime	2125	2130	5	Black Lime
1410	1445	35	Gray Lime	2130	2200	70	Sand
1445	1480	35	Lime	2200	2215	15	Lime
1480	1495	15	Anhydrite & Lime	2215	2225	10	Sand
1495	1510	15	Brown Lime	2225	2245	20	Lime
1510	1518	8	Anhydrite & Gyp	2245	2255	10	Sand
1518	1560	42	Anhydrite & Lime				
1560	1585	25	Brown Lime				
1585	1655	70	Anhydrite & Sandy Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

.....**November 19, 1952**.....(Date)
Company or Operator.....**Jenkins & McQueen**.....Address.....**1009 Colecord Bldg., Okla. City, Okla**
Name.....*A. D. Sankey*.....Position or Title.....**Office Manager**.....