



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

IN REPLY REFER TO:

RECEIVED

JUL 11 1957

P. O. Box 187
Artesia, New Mexico

Oil Cons. Comm.
ARTESIA OFFICE

July 8, 1957

Mr. E. A. Hanson
P. O. Box 852
Roswell, New Mexico

Re: Oil and Gas Lease
LC 072015

Dear Sir:

Your "Subsequent Report of Abandonment" dated June 20, 1957, covering your well No. 1-McBride located (1980 feet from south and east lines of) section 34, T. 20 S., R. 27 E., Wildcat Area, Eddy County, New Mexico, is hereby approved.


Very truly yours,

(Orig. Sgd.) JOHN A. FROST

John A. Frost
District Engineer

JAF:mm

Copy to: USGS
Carlsbad, New Mexico



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Santa Fe**Lease No. **LC 072015**

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 20, 1957

Well No. **1 McBride** is located **1980** ft. from **N** line and **1980** ft. from **E** line of sec. **34****C NW 1/4 SE 1/4 Sec. 34**
(1/4 Sec. and Sec. No.)**T. 20 S.**
(Twp.)**R. 27 E.**
(Range)**N. M. P. M.**
(Meridian)**Wildcat**
(Field)**Eddy**
(County or Subdivision)**New Mexico**
(State or Territory)The elevation of the derrick floor above sea level is **3232** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to total depth of 150' with rotary rig using air. At 150', circulation was lost and an attempt was made to re-establish circulation using mud. Approximately 7500 gallons of very heavy mud was pumped back into the formation without success. The hole was then filled with 5 sacks of cement, plugging the interval 110' to 150'. A bridge was then set at the interval from 105' to 110' and cement circulated to the surface. A regulation marker was then set on the surface.

RECEIVED
JUN 26 1957

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **ERNEST A. HANSON**Address **P. O. Box 852****Roswell, New Mexico**By **Harry F. Schram**Title **Geologist, Ernest A. Hanson**