

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

CLSF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole, Replug		AUG - 5 1992	
2. NAME OF OPERATOR Bill Taylor		O. C. D.	
3. ADDRESS OF OPERATOR 1106 N. Country Club, Carlsbad, NM 88220		WELLS OFFICE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 5610/5 & 990' FWL		5. LEASE DESIGNATION AND SERIAL NO. NM01119	
14. PERMIT NO. 30-015-01064		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3198' GL	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)		7. UNIT AGREEMENT NAME	
		8. FARM OR LEASE NAME Welch-Yates C Fed.	
		9. WELL NO. Riggs-Welch #4	
		10. FIELD AND POOL, OR WILDCAT Cedar Hills Yates	
		11. SEC., T., S., M., OR BLK. AND SURVEY OR AREA 4-T21S, R27E, NMPM	
		12. COUNTY OR PARISH EDDY	
		13. STATE NM	

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

Replugging Actions XX
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

The Riggs-Welch #4 was drilled out to 606', 8' into a solid bottom plug. Gel and loss circulation material were pumped through 2 3/8" tubing into the hole, and placed between plugs.

- 7/14/92: set tubing at 605 1/2' and pumped 25 sack cement plug: witnessed by NMOCD's Johnny Robinson & BLM's Gene Hunt; raised tubing to 433' and pumped second 25 sack cement plug with 1/2 bag cedar chips; small amount gel/loss circulation material circulated: witnessed by NMOCD's Johnny Robinson;
- 7/15/92: tagged second plug at 262', set tubing at 150' and pumped on third 25 sack cement plug until gel/loss circulation material followed by cement circulated well to pit; running in tubing, tagging cement, and cementing witnessed by BLM's Duncan Whitlock;
- 7/17/92: old 4" surface marker was reset/cemented at the surface;

A 5" pipe with proper well identification has been placed over the old 4" marker, the Cable Tool cuttings pit has been filled, site releveled, and the well/site reabandoned.

18. I hereby certify that the foregoing is true and correct

SIGNED Bill Taylor

TITLE Operator

DATE 7/21/92

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE 8/4/92

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side