Form 31605			Form approved.	c	
November 1983) Formerly 9331)	UNI J STATES DEPARTMENT OF THE INTEI	SUBMIT IN TRIPLIC E.	Budget Bureau No. Expires August 31	. 1985	
omeny (			5. LEASE DESIGNATION AND	D BERIAL NO	
······	BUREAU OF LAND MANAGEME	NI	NM DOMI9		
	IDRY NOTICES AND REPORTS	g hack to a different reservoir	6. IF INDIAN, ALLOTTRE OF		
OIL GAS WELL WELL	Water Disposal	Well JEP I II J3 AM	TOUNIT AGREEMENT NAME		
NAME OF OPERATOR	/	CZ	8. FARM OR LEASE NAME		
George	D. Riggs	SEPA113 '90	9. Welch Feder	ral	
P, Q, BO LOCATION OF WELL (F See also space 17 bel At surface	x 116 Carlebad, NM 88 Report location clearly and in accordance with an ow.)	1221 C. C. D. ny State ARTELICA, COMPLEE	10. FIELD AND POOL, OR W Cedar Hills 11. SRC, T., R., M., OR BLK.	s Yrt≈S	
1650/S -	& 1650/E	<b>^</b> ·	SURVET OR ARMA	1540	
PERMIT NO.	15 ELEVATIONS (Show whether	DE BT (D) ata )	Sec 5-T21S-R27	7E, NMPM	
		DF, RT, GR. ECC.)	12. COUNTY OR PARISH 13	3. STATE	
	3270' GL		EDDY	NM	
i.	Check Appropriate Box To Indicate	Nature of Notice, Report, or O	Yher Data		
NOTICE OF INTENTION TO :		SUBSEQU	SUBSEQUENT REPORT OF :		
TEST WATER SHUT-O	FF PULL OR ALTER CASING	WATER SHUT-OFF	BEPAIRING WELL		
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASIN	a	
SHOOT OR ACIDIZE	ABANDON •	SHOOTING OR ACIDIZING	ABANDONMENT*	×	
REPAIR WELL	L CHANGE PLANS	(Other)			
(Other)	1	(NOTE: Report results )			

nent to this work.) \*

The above well was plugged and abandoned in the following manner, using Halliburton:

518' of 5 1/2" Casing was left in hole, with holes @ 100', 242', & 330'. 3" Tubing was cut off at 536' and 2 3/8" tubing was run in the hole to place cement. 3 sx. 20-40 sand and 10 BBLs Gel with 2 sx. Multi Seal were pumped to seal formation, followed by 100 sx. Premem Plus 3 % CaCl with 1/2# Flocele per sx. Pressured to 300#s, and waited 2 hrs. Tagged cement at 430'. Placed 3 sx. sd. followed by 35 sx. PP, 3% CaCl, and waited 1 1/2 hrs. Tagged cement at 150'. Placed 35 sx. PP, 3% CaCl, and circulated to surface; cement fell back while waiting 1 1/2 hrs. Placed loss circulation material and 30 sx PP, 3% CaCl, and circulated cement to surface; cement held. PLACED SURFACE MARKER.

> Post ID-2 9-21-90 1×17

P & A, 1-9-90, witnessed by Mr. Robinson of the NMOCD.

Site has been cleaned and is ready for abandonment inspection.

I hereby certify that the foregoing is true and co SIGNED <u>Job Rugg</u>	TITLE Operater	DATE (19-06-90
(This space for Federal or State office use)		DATE 9-11-90
CONDITIONS OF APPROVAL, IF ANY: Approved as to pluga signafic a wall bore. Lizbility and stational signafic audit surface restoration is conducted.	*See Instructions on Reverse Side	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any descent a