



## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	70	70	Red rock and gyp <i>sum</i>
70	100	30	Water and sand
100	125	25	Heaving sand
125	200	75	Sand
200	250	50	Sand and sheets of mud
250	300	50	Sand, red clay and gyp <i>sum</i>
300	350	50	Red clay, gumbo and gyp shells
350	400	50	Red bed and gyp
400	432	32	Red rock, gyp
432	592	160	Salt. TOP of salt 432
592	612	20	Lime
612	620	8	Broken lime and gyp
620	700	80	Lime
700	720	20	Hard, grey lime. Set <del>740D</del> at 712', cemented with 50 sacks cement around shoe, and 25 sacks through braden-head.
720	755	35	Hard, brown lime
755	765	10	Medium brown lime
765	775	10	Broken lime
775	780	5	Blue shale
780	788	8	Lime, grey, broken
788	795	7	Blue shale and broken lime
795	807	12	Shale, broken lime and sand
807	816	9	Sandy lime, Show OIL 795-807
816	830	14	Broken sandy lime
830	875	45	Broken sandy lime and shale
875	885	10	Hard, grey lime.
885	895	10	Broken lime and shale
895	900	5	Sandy shale
900	908	8	Hard, light grey lime.
		T.D.	